



**POWER
SYSTEMS, INC.**

In the world of power transmission and distribution, look to Hubbell.

**Interactive
eCatalog**

[Catalog Home](#)

Product Datasheet

OHIO/BRASS

215LE43T -- Load Break Elbow



Load Break Elbow, 200 Amp, 15
kV, with Test Point, Long
Bimetal Contact

Product Specifications

Product Type	Load Break Elbows
With Test Point	Yes
PROBELOK ® Connectors	No
Cable Insulation Range	.635" to .905"
With Seal Kit	No
Current Rating	200 A
Voltage Class	15 kV
Cable Insulation Diameter Minimum	.635 in (16.1 mm)
Cable Insulation Diameter Maximum	.905 in (23,0 mm)
Type of Connector	Long Bimetal
Basic Impulse Level	95 kV

Corona Extinction (3pC)	11 kV
AC Withstand Voltage (1 min)	34 kV
DC Withstand Voltage (15 min)	53 kV
Material Type	Standard
Standard Package	20
Standard Package Unit	Each
Min Order Qty	20
Weight / Ea.	2.75 lbs
Type	200Amp Load Break
Voltage Type	15 kV 200A Load Break
Stranded or Compressed / Solid or Compacted	#2 / #1
Stranded or Compressed	#2
Solid or Compacted	#1
Integral Seal	No
Sales Drawing	View Drawing

Notes

N/A

Features

N/A

Compressed Product Number

215LE43T

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.