



Product Datasheet

CHANCE

M3D67BCR -- M3 Switch



25 kV, 125kV, 600 A, Single-Phase Hookstick Disconnect Switch

Product Specifications

| | |
|---|--|
| Overhead Product | Single Phase - Distribution Disconnect Switch (Crossarm Mounted) |
| Voltage(BIL) | 25kV (125kV) |
| Rated Current | 600 A |
| Insulator Type | ESP™ Polymer (2 1/4" Bolt Circle) |
| Base Type | Distribution Base, Serrated Slots |
| Carriage Bolt Length | 8" (203 mm) |
| Captive Hardware | Yes |
| Terminal Connectors (ATC 1343) | No |
| Open Position Latch (160° Opening) | No |
| Bypass Studs | Yes |
| Nominal Voltage | 25 kV |
| Maximum System Voltage | 27kV |
| BIL (LIW) | 125kV |
| Rated 60 Htz Withstand; Dry (Wet) | 50kV (45kV) |
| Continuous Current Rating | 630 A |
| 8hr Emergency Overload | 1080 A |
| Momentary Current Rating | 40kA, asymmetrical |
| Short Time Withstand Current (2 sec) | 25kA, symmetrical |
| Short Time Withstand Current (3 sec) | 16kA, symmetrical |
| Maximum Temperature Rise @ 600A | 28°C |
| Insulator Color | Dark Gray |
| Leakage Distance (Insulator) | 21.9" (556.3mm) |
| Dry Arcing Distance (Insulator) | 21.9" (556.3mm) |
| Cantilever (Insulator) | 8.1" (205.7mm) |
| Tension (Insulator) | 1,000 Lbs (4.45kN) |

| | |
|-------------------------------------|---|
| Torsion (Insulator) | 5000 Lbs (22.24kN) |
| Compression (Insulator) | 3,000 in Lbs (339 N-M) |
| Base Material | Galvanized Steel per ASTM A153 |
| Base Description | Distribution Base, Serrated Slots with four 3/8" Carriage Bolts and backstrap |
| Dead-ending (Working Load) | 8,000 Lbs |
| Blade(s) | Solid Copper (two blade truss-member) |
| Hinge(s) | Silver / Silver |
| Contact(s) | Silver / Silver |
| Terminal Pads | NEMA two-hole, Tin-plated Copper |
| Captive Hardware Description | Consist of 4 each: 1/2" 13 Stainless Steel Splined Bolt, 1/2" Lockwasher and Bronze Nut |
| Governing Standards | All Applicable ANSI/IEEE Standards |
| Drawing | Click HERE to view drawing of switch |
| Crated Weight | 19.6 lbs |
| Material Type | Non-Standard |
| UPC Code | 09635932123 |
| Standard Package | 1 |
| Standard Package Unit | Each |
| Min Order Qty | 1 |
| Weight / Ea. | 19.6 lbs |

Compressed Product Number

M3D67BCR

[Catalog Home](#)



[Warranty Info](#) | [Trademarks](#) | [Terms of Use](#)

All contents Copyright © 2007 Hubbell Power Systems, Inc. All rights reserved.

NOTE: Because Hubbell has a policy of continuous product improvement, we reserve the right to change design and specifications without notice.