


Catalog Number: Item Description: UPC Code: U4801-XL-ALT 200A 4T RL HD LVR OU 784572496286


Brand Name:	Milbank
Туре:	Ringless Meter Socket
Application:	Meter Socket
Standard:	UL Listed
Voltage Rating:	600 Volts Alternating Current
Amperage Rating:	200 Continuous Ampere
Phase:	1 Phase
Frequency Rating:	60 Hertz
Number Of Cutouts:	0
Cable Entry:	Overhead and Underground
Terminal:	Lay In Line Side and Lay in Load Side
Mounting:	Surface Mount
Enclosure:	Type 3R, G90 Galvanized Steel with Powder Coat Finish
Additional Specificatio	ns: Number of Jaws:4 Terminal




Number of Jaws:4 Terminal Hub Opening and Closing Plates:Small Closing Plate Hub Opening and Closing Plates:Small Closing Plate

FEATURE TABLE		
ITEM	QTY	DESCRIPTION
Α	5	U/L MNTG.EMBOSS
В	1	1/4 SOLID K.O.
С	1	1/4, 1/2 CONC. K.O.
D	2	1, 1¼, 1½, 2, 2½ CONC. K.O.
Е	4	1¼, 1½, 2, 2½, 3 CONC. K.O.







Version:

All dimensions are +/- 1/16". Drawing views are not to scale.

Utility requirements for this equipment may vary. Always consult the serving utility for their requirements prior to ordering or installing this equipment. This product must be installed by a licensed electrician. Installation of this equipment may require local electrical inspector approval.