

Product availability : Stock - Normally stocked in distribution facility



Price\* : 1487.00 USD



### Main

Product or component type	Circuit breaker
Range of product	PowerPact H
Trip unit technology	Electronic standard Micrologic 3.2 LI
Breaking capacity code	D

### Complementary

Line Rated Current	100 A
Poles description	3P
Breaking capacity	18 kA at 480 V AC 25 kA at 240 V AC 14 kA at 600 V AC
System Voltage	600 V AC
[Ics] rated service short-circuit breaking capacity	80 %
Mounting mode	Unit mount
Electrical connection	Lugs load Lugs line
AWG gauge	AWG 14...AWG 3/0 (aluminium/copper)

### Environment

Product certifications	CCC CE CSA IEC UL listed
Ambient air temperature for operation	104 °F (40 °C)

### Ordering and shipping details

Category	01107 - H/J ELEC TRIP UNIT MOUNT BREAKER/SW
----------	---

Discount Schedule	DE2
GTIN	00785901548324
Nbr. of units in pkg.	1
Package weight(Lbs)	6.2800000000000002
Returnability	Y
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1132 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Available

### Contractual warranty

Warranty period	18 months
-----------------	-----------