



Main

Range of product	Altivar Lexium
Product or component type	Braking resistor
Range compatibility	Altivar Machine ATV320 Lexium 32i Lexium 15 Altivar 32 Lexium 32 Lexium 52
Product compatibility	ATV32H018M2 ATV32H037M2 ATV32H037N4 ATV32H055M2 ATV32H055N4 ATV32H075M2 ATV32H075N4 ATV32HU11N4 ATV32HU15N4 ATV32HU22N4 Variable speed drive ATV320 motor at 2.2 kW, 525...600 V, three phase Variable speed drive ATV320 motor at 0.37 kW, 200...240 V, single phase Variable speed drive ATV320 motor at 1.5 kW, 380...500 V, three phase Variable speed drive ATV320 motor at 0.75 kW, 525...600 V, three phase Variable speed drive ATV320 motor at 0.18 kW, 200...240 V, single phase Variable speed drive ATV320 motor at 0.55 kW, 200...240 V, single phase Variable speed drive ATV320 motor at 2.2 kW, 380...500 V, three phase Variable speed drive ATV320 motor at 1.5 kW, 525...600 V, three phase Variable speed drive ATV320 motor at 0.75 kW, 200...240 V, single phase Variable speed drive ATV320 motor at 0.37 kW, 380...500 V, three phase Variable speed drive ATV320 motor at 0.55 kW, 380...500 V, three phase Variable speed drive ATV320 motor at 0.75 kW, 380...500 V, three phase Variable speed drive ATV320 motor at 1.1 kW, 380...500 V, three phase
Ohmic value	100 Ohm
Continuous power	100 W
Average power available	25 Wat 122 °F (50 °C)

Cable length	9.84 ft (3 m)
--------------	---------------

Complementary

Energy peak	4400 Jat 115 V 2700 Jat 480 V 3000 Jat 400 V 4500 Jat 230 V
Protection type	Thermal protection via the servo drive
Product weight	1.68 lb(US) (0.76 kg)

Environment

Ambient air temperature for operation	32...122 °F (0...50 °C)
Ambient air temperature for storage	-13...185 °F (-25...85 °C)
IP degree of protection	IP65
IP degree of protection	IP65

Ordering and shipping details

Category	18263 - LEXIUM 32 ACCESSORIES
Discount Schedule	PC51
GTIN	00785901939931
Nbr. of units in pkg.	1
Package weight(Lbs)	1.99
Returnability	Y
Country of origin	DE

Contractual warranty

Warranty period	18 months
-----------------	-----------