

Product availability : Stock - Normally stocked in distribution facility



### Main

Product or component type	Circuit breaker
Range of product	QO
Line Rated Current	30 A
System Voltage	240 V AC
Mounting mode	Plug-in
Poles description	3P
Circuit breaker type	Standard
Circuit breaker application	HACR rated
Electrical connection	Box lugs

### Complementary

Breaking capacity	10 kA at: 240 V AC
Number of spaces required	3
Provided equipment	48 in lead
AWG gauge	AWG 12...AWG 2 (aluminium) AWG 14...AWG 2 (copper)
Height	4.55 in
Depth	2.91 in
Width	2.25 in

### Environment

Product certifications	CSA UL listed
Ambient air temperature for operation	104 °F (40 °C)

## Ordering and shipping details

Category	09650 - POWERLINK QO(B)PL BREAKERS
Discount Schedule	DE8A
GTIN	00785901956969
Nbr. of units in pkg.	1
Package weight(Lbs)	1.4000000000000001
Returnability	Y
Country of origin	MX

## Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1323 - Schneider Electric declaration of conformity <a href="#">Schneider Electric declaration of conformity</a>
REACH	Reference not containing SVHC above the threshold <a href="#">Reference not containing SVHC above the threshold</a>
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

## Contractual warranty

Warranty period	18 months
-----------------	-----------