



Center Plate Configurations

- Allows for 3 duplexes or up to 18 data/ AV jacks; Other combinations possible
- Accepts third party AV devices (i.e. Extron®, Crestron®, FSR®)
- Standard NEMA spacing between devices



Perimeter Plate Configurations

- Available in pre-wired duplexes or openings to accommodate third party AV devices
- Multiple duplexes can be wired in the supplied junction box or independently



Center Sub-Plates - Single Gang

Description/Cat. No.	Sub-Plate	Description/Cat. No.	Sub-Plate
Blank cover plate S1R8CSPB		(2) Extron MAAP openings S1R8CSPC	
(1) 1 unit Hubbell iSTATION opening S1R8CSPD		(1) 1.5 unit Hubbell iSTATION opening (See section AA for modules) S1R8CSPE	
(1) 1.60" opening for 20A & 30A Twist-Lock® S1R8CSPG		(1) Duplex opening S1R8CSPI	
(1) 1.40" opening for simplex or 15A Twist-Lock S1R8CSPJ		(1) Style Line® decorator opening S1R8CSPK	
(1) Hubbell Jack opening and (3) Jack KOs with Label Field S1R8CSP4DJ			

Perimeter Sub-Plates

Description/Cat. No.	Sub-Plate	Description/Cat. No.	Sub-Plate
Blank cover plate S1R8PSPU		Single Extron MAAP opening S1R8PSPV	
Pull through with 1" bushing opening S1R8PSPW		Single Extron AAP opening S1R8PSPX	
(1) 1 unit Hubbell iSTATION opening (see section AA for modules) S1R8PSPY		Dual 20A pre-wired power cubes; one circuit (supplied with isolated ground sticker) S1R8PSPZ S1R8PSPZ25 (25 foot leads)	
Dual 20A pre-wired power cubes; one circuit (supplied with isolated ground sticker); marked with "Controlled"; (18 inch leads) S1R8PSPZC		Dual 20A pre-wired power tamper resistant cubes; one circuit (supplied with controlled and isolated ground stickers); (18 inch leads) S1R8PSPZTR	

Center Sub-Plates - Two Gang

Desc/Cat. No.	Sub-Plate	Desc/Cat. No.	Sub-Plate	Desc/Cat. No.	Sub-Plate	Desc/Cat. No.	Sub-Plate	Desc/Cat. No.	Sub-Plate
Two gang; (4) Extron AAP openings S1R8CSPA		Two gang; 3 unit Hubbell iSTATION opening (See section AA for modules) S1R8CSPL		Two gang; (2) Style Line Decorator openings S1R8CSPM		Two gang; device depth extension collar (for use with 3rd party data up to 2.5" depth) S1R8CSPEXT		Two gang; (2) Hubbell Jack openings and (4) Jack KOs with Label Field S1R8CSP6DJ	

Center Sub-Plates - Three Gang

Description/Cat. No.	Sub-Plate	Description/Cat. No.	Sub-Plate	Description/Cat. No.	Sub-Plate
Three gang; blank cover plate S1R8CSPN		Three gang; device depth extension collar (for use with 3rd party data up to 2.5" depth) S1R8CSPEXT3		Three gang extender with two gang opening; device depth extension collar (for use with 3rd party data up to 2.5" depth) S1R8CSPEXT32	

Note: Rectangular Sub-Plates are for center compartments, crescent Sub-Plates are for perimeter compartments and are not inter-changeable. See page R-14 for covers and accessories. Extron® is a registered trademark of Extron Electronics. Crestron® is a registered trademark of Crestron Electronics, Inc. FSR® is a registered trademark of FSR Inc.

Dimensions in Inches (mm)