30 Amp, 125/250 and 3Ø 250 Volts AC, 3 Pole, 3 Wire, Non-Grounding and 3 Pole, 4 Wire, Grounding



30A 125/250V AC NEMA L10-30R	30A 125/250V AC NEMA L14-30R 2 (2) HP	30A 3Ø 250V AC NEMA L15-30R 3 HP

Connector Bodies

Watertight Safety-Shroud®

IP66 SUITABILITY — UL Type 4X, 12

Description	Cord Dia.	Catalog Number		
Black Valox® housing, white Valox clamps.	.350"-1.150" (9-29)	—	HBL2713SW	HBL2723SW
Reverse service, black Valox housing, white Valox clamps (use with HBL2715SWR) (not shown).	.350"-1.150" (9-29)	—	HBL2713SR	—

Insulgrip®

IP20 SUITABILITY

Description	Cord Dia.	Catalog Number		
Black and white nylon.	.350"-1.150" (9-29)	—	HBL2713	HBL2723
Black and white nylon, spring termination.	.350"-1.150" (9-29)	—	HBL2713ST	HBL2723ST
Spring termination, all black.	.350"-1.150" (9-29)	—	HBL2713STBK	—
Black and white nylon (not shown).	.300"-.950" (7.6-24.1)	HBL2663	—	—
Corrosion resistant, yellow nylon.	.350"-1.150" (9-29)	—	HBL27CM13	HBL27CM23
All black nylon.	.350"-1.150" (9-29)	—	HBL2713BK	—

Note: See pages C-52 and C-53 for accessories.

Receptacles

Watertight Safety-Shroud

IP66 SUITABILITY — UL Type 4X, 12

Description	Catalog Number		
Gray Valox housing and flange, back wired.	—	HBL2710SW	HBL2720SW

Note: See page C-54 for accessories.

Safety-Shroud® Twist-Lock

IP20 SUITABILITY

Description	Catalog Number		
Gray Valox angle housing, one gang, back wired.	—	HBL2710AR	HBL2720AR
Gray Valox surface mounting, one gang, back wired.	—	HBL2710SR	HBL2720SR
Gray Valox semi-flush, two gang, back wired.	—	HBL2710SR2	HBL2720SR2

Single Flush Receptacles

IP20 SUITABILITY


Description	Catalog Number		
Black nylon face, back and side wired.	—	HBL2710	HBL2720
Black and white nylon, spring termination.	—	HBL2710ST	HBL2720ST
Black nylon face, back and side wired (not shown).	HBL2660	—	—
Isolated ground, orange nylon face, back and side wired.	—	IG2710	IG2720
Isolated ground, orange face, spring termination.	—	IG2710ST	IG2720ST
Ring terminal connection.	—	HBL2710RT	HBL2720RT

Note: See page C-52 for accessories.


Insulgrip Flanged Receptacles

Description	Catalog Number		
Nylon casing, back wired.	—	HBL2716	HBL2726
Nylon casing, back wire, spring termination.	—	HBL2716ST	HBL2726ST


Note: See page C-52 for accessories.



HBL2716



HBL2710



HBL2710SR2

Valox® is a trademark of SABIC Innovative Plastics, acquired from General Electric Company.


Fed. Spec.




HBL2713SW



HBL2713



HBL2710SW



HBL2720ST



HBL2710SR

Dimensions in Inches (mm)