

# PHOTOCONTROLS

## 1/2" Conduit Mount

Specification Grade, Die Cast Aluminum  
2110 Series



### SPECIFICATIONS

- **ON/OFF:** Turn ON is 1 to 5fc, Turn OFF is 3 to 15fc, without the slide in position. ON/OFF adjustment is easily made by moving a slide cover. No tools required.
- **Time Delay:** ON and OFF.
- **Cell:** Cadmium sulphide, epoxy conformal coated 1/2" diameter. Model 2117 and 2119A has a 1" photocell.
- **Contacts:** Remain closed between dusk and dawn. (The unit fails in the ON position).
- **Lead Wires:** Three color coded, minimum 6" wire leads, #16AWG, rated for 105 °C. 2119A five color coded wires, 2117 #10AWG red and black.
- **Power Consumption:** Averages under 1 watt.
- **Temperature Range:** -40 °F to +140 °F (-40 °C to +60 °C).
- **Fail Mode:** ON.
- **Warranty:** 5 years.

### APPLICATIONS

- Parking lot lighting.
- Building perimeter lighting.
- Outdoor signage.

### FEATURES

- **Sensor:** Conformal coated cadmium sulphide photocell resists effects of moisture and airborne contaminants. Photocell responds to the light spectrum near to that of a human eye.
- **Operation:** Delay of up to two minutes to prevent false switching due to light from passing vehicles, lightning, etc.
- **Standards:** Meets ANSI/UL773A.
- **Housing:** Die cast aluminum housing and base. Gasketed for weather protection.
- **Energy Savings:** Works with screw base CFLs.

### ACCESSORIES

- **73866:** See page 434.



| CAT. NO.          | CERTIFICATION | UPC CODE | VOLTAGE<br>VAC 50/60Hz | RATING           |                    |                   |
|-------------------|---------------|----------|------------------------|------------------|--------------------|-------------------|
|                   |               |          |                        | TUNGSTEN         | BALLAST            | LED               |
| 2115              | cULus         | 60032    | 120                    | 2000W            | 1800VA             | 600VA             |
| 2116              | cULus         | 60033    | 208-277                | 3470-4620W       | 2080-2770VA        | 1040-1385VA       |
| 2117              | CSA           | 60037    | 120                    | 3000W            | 3000VA             | —                 |
| <b>NEW!</b> 2119A | cULus         | 62035    | 120/208-277            | 2000W/3470-4620W | 1800VA/2080-2770VA | 600VA/1040-1385VA |