

XVLA134

pilot light Ø8 - IP40 - red - protruding LED
included - 24V - faston

Product availability : Stock - Normally stocked in distribution facility



Main

| | |
|---------------------------|--|
| Range of product | Harmony XVL |
| Product or component type | LED pilot light with black bezel |
| Component name | XVL |
| Mounting diameter | 0.31 in (8 mm) |
| Light source | Protruding LED |
| Light block colour | Red |
| Protection type | Integral ballast resistor Built-in by diode |
| [Us] rated supply voltage | 24 V |
| IP degree of protection | IP40 conforming to IEC 60529 IP40 conforming to NF C 20-010 |

Complementary

| | |
|-------------------------------|--|
| Supply circuit type | DC |
| Connections - terminals | Tag for Faston connectors : 2.8 x 0.5 mm Tag for soldering connectors |
| Current consumption | 18 mA |
| [Ui] rated insulation voltage | 50 V conforming to IEC 60947-1 |
| Bulb lifespan | >= 100000 h |
| Nominal voltage limit | 0.8...1.1 Un |
| Terminals description ISO n°1 | (X1-X2)PL |
| Height | 0.47 in (12 mm) |
| Width | 0.47 in (12 mm) |
| Depth | 1.34 in (34 mm) |
| Product weight | 0.01 lb(US) (0.003 kg) |

Environment

| | |
|---------------------------------------|--|
| Product certifications | CSA UL |
| Protective treatment | TC |
| Ambient air temperature for operation | -13...158 °F (-25...70 °C) |
| Ambient air temperature for storage | -40...158 °F (-40...70 °C) |
| Overvoltage category | Class 3 conforming to IEC 60536 Class 3 conforming to NF C 20-030 |

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 22460 - PUSHBUTTONS 22MM (PLASTIC) |
| Discount Schedule | CS2 |
| GTIN | 00785901247968 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 0.01 |
| Returnability | Y |
| Country of origin | ES |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|