



# 9370-FR



VIDEO

## Product Description

4" dia. round fan support box for use with nonmetallic sheathed cable

**Catalog #:** 9370-FR

**Width:** 4 in.

**Depth:** 1-1/2 in.

**Volume:** 8 cu. in.

**Type of Installation:** Old or New Work  
**Round Ceiling Box**

**Carton Quantity:** 24

**Carton Weight:** 6 lb.

**UPC:** 085339766001

**UNSPSC:** 39121316

**Country of Origin:** United States of America

## FEATURES

1/2" deep base with side cube wiring capacity, fan/fixture screws for joist mounting

## APPLICATION

New and old work residential construction 2 HR fire resistive walls and ceilings (70 lbs. fan support and 110 lbs. fixture support)

## STANDARDS

ANSI / UL 514C: File No. E30594



## FIRE CLASSIFICATION

### Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

*Note: Products must also be certified to: ANSI / UL 514C*

### Fire Resistance Classification in Wall Assemblies 2-Hours or less

Shall be separated by a horizontal distance of not less than 3 inches

### Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 1/2 inches

*Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)*

## COLOR

Beige/tan

## MATERIAL

Fiberglass reinforced polyester BMC

## MOUNTING

Bottom mount

## ADDITIONAL MATERIALS

Plated carbon steel fasteners

Nonmetallic pop-in cable clamp

## SUPPORT RATING

110 lbs fixture support and 70 lbs fan support