

# Kwiko™ A Sealing Cement and Filler

## For use in Sealing Fittings and Sealing Hubs

See specific sealing fitting and sealing hubs for quantities required.

### Applications

- Fiber filler-makes dams around and between all conductors to prevent sealing compound from leaking while being poured in its liquid state.

### Features

- Kwiko™ A sealing cement is a specially formulated water soluble powder. Mixed to the proper proportions, it is poured in sealing fittings and hardens to contain and restrict the passage of gases and explosions in classified areas.

### Options

- For larger quantities of Twin Pack® Sealing Cement, contact your local sales representative.



EYCK5LB



EYFK4



AC1F01-A0Z

# Kwiko™ A Sealing Cement and Filler

For use in Sealing Fittings and Sealing Hubs

See specific sealing fitting and sealing hubs for quantities required.

	Weight Grams (Ounces)	Volume When Set dm <sup>3</sup> (in <sup>3</sup> )	Catalog Number
--	--------------------------	---	-------------------

**Kwiko™ A Sealing Cement Mixing Ratio: 2 parts cement to 1 part water**



	453.6 (16.00)	0.38 (23.00)	EYCK160Z
	2268.0 (80.00)	1.89 (115.00)	EYCK5LB

## Fiber Filler

Filler is used to make dams to prevent cement from leaking while in fluid state.



	113.4 (4.00)	—	EYFK4
	226.8 (8.00)	—	EYFK8
	453.6 (16.00)	—	EYFK16

## Kwiko™ A Sealing Cement and Fiber Filler Kits



Cement	453.6 (16.00)	377.0 (23.00)	AC1F01-A0Z
Fiber	28.4 (1.00)		

## Approximate amount of fiber filler required per hub — For 25% fill ①

Hub Size (Inches)	Weight Grams (Ounces)	Hub Size (Inches)	Weight Grams (Ounces)	Hub Size (Inches)	Weight Grams (Ounces)
1/2	0.9 (0.03)	1-1/2	14.2 (0.50)	3-1/2	85.1 (3.00)
3/4	1.7 (0.06)	2	28.4 (1.00)	4	127.6 (4.50)
1	3.7 (0.13)	2-1/2	42.5 (1.50)	5	198.5 (7.00)
1-1/4	7.1 (0.25)	3	56.9 (2.00)	6	284.1 (10.00)

① For 40% expanded fill seal fittings, double the amount of fiber filler shown.