


RIGID BODIES AND ASSEMBLIES

LB Assembly
N/A

C13



Catalog #: RLB250

APPLICATIONS

For use with threaded rigid/IMC conduit for pulling access or to split a run into multiple directions. Removable cover allows access for maintenance and making taps and splices to conductors.
N/A

PRODUCT FEATURES

- Durable die cast aluminum construction
- Premium powder coat finish
- Includes NBR synthetic rubber gasket
- Stamped aluminum cover
- Combination head screw

UL LISTED

File E331564

NEMA

NEMA 3R rated

NEC

2014 NEC® compliant

GENERAL PRODUCT INFORMATION

Trade Size: 2-1/2 in.

DRAWING DIMENSIONS

Dimension A: 12.83 in.
 Dimension B: 4.49 in.
 Dimension C: 5.31 in.
 Dimension D: 11.250 in.
 Dimension E: Tapped holes #5/16UNC-2B
 Thread Spec. F: 2-1/2-8NPT
 Dimension G: 2.459 in.

PRODUCT MEASUREMENTS

Cubic Inches (cm³): 157.3 (2578)

PACKAGING

Package Type: Carton
 Ship Carton Qty.: 1
 Product UPC-A Labeled: Yes
 Weight (Lbs. Per/C): 410.00
 Ship Carton Length (in.): 14.13
 Ship Carton Width (in.): 5.88
 Ship Carton Height (in.): 7.00
 Ctn Weight (Lbs.): 4.10
 UPC Number: 092326213103
 I2of5: 30092326213104