PYRAMEX

H2X OPTIONS | H2MAX OPTIONS | BALLISTIC | READER OPTION | FOAM PADDING | INTERCHANGE TEMPLE/STRAP | INCLUDES STRAP

XSG®

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020 | MIL-PRF-32432

Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

VARIATIONS

Black Frame | 4 Variations

GB4010ST	Clear H2X AF
GB4010STM	Clear H2MAX AF
GB4020ST	Gray H2X AF
GB4080ST	I/O Mirror AF

XSG® Reader

ANSI/ISEA Z87.1-2020 + | CAN/CSA Z94.3-2020

Flame resistant foam padding // Strap has quick-fit retainer // Interchangeable temples and strap included // Custom imprinting available

VARIATIONS

Black Frame | 3 Variations

GB4010STR15	Clear H2X AF	+1.5 Mag
GB4010STR20	Clear H2X AF	+2.0 Mag
GB4010STR25	Clear H2X AF	+2.5 Mag

XSG® Kit

ANSI/ISEA Z87.1-2020 + | MIL-PRF-32432

Interchangeable lenses, temples, and strap // Black nylon case for storage // Passes Ballistic MIL-PRF-32432 High Velocity Impact standards // Custom imprinting available

VARIATIONS

Black Frame | 3 Interchangeable Options

GB4010KIT

Clear H2X AF Gray H2X AF Amber H2X AF

PYRAMEX

H2X OPTIONS | H2MAX OPTIONS | BALLISTIC | READER OPTION | FOAM PADDING | INTERCHANGE TEMPLE/STRAP | INCLUDES STRAP

XSG® and XSG Kit

General Specifications

Weight: 28 gm

PD: 68 mm

Bridge: 13.7 mm

Lens Base: 8 curve

Lens Size Diagonal: 66.3 mm

Lens Size Vertical: 44 mm

Lens Thickness: 2.3 mm

Overall Length (lens - tip): 163 mm

Overall Width (hinge - hinge): 136.5 mm

Closest Point Between Lens: 18.5 mm

Strap Length: 420 mm

Materials

Lens: Polycarbonate

Foam: Polycarbonate & Ethylene Vinyl Acetate

Frame: Nylon

Temples: Polycarbonate & Polyvinyl Chloride

Strap: Polyester

Screw: Stainless Steel

Nose Piece: Ethylene Vinyl Acetate

Part No.	Lens Marking	Temple Marking
GB4010ST	P Z87 + U6	P Z87 + / P c SEI Z94.3
GB4010STM	P Z87 + U6 X	P Z87 + / P c SEI Z94.3
GB4020ST	P Z87 + U6 L2.5	P Z87 + / P c SEI Z94.3
GB4080ST	P Z87 + U6 L1.7	P Z87 + / P c SEI Z94.3
GB4010KIT	P Z87 + U6	P Z87 + / P c SEI Z94.3
	P Z87 + U6 L2.5	
	P Z87 + U6	

Lens Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

X: Tested Anti-Fog

UV Filter Transmittance

U6: .01% Max Effective Far UV • .1% Max Near UV

Visible Light Filters

L1.7: 55% Max. Visible Light

L2.5: 29% Max. Visible Light

Temple Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

c SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices

Product markings may vary // Updated as of 01.26

XSG® Readers

General Specifications

Weight: 35 gm

PD: 68 mm

Bridge: 13.7 mm

Lens Base: 8 curve

Lens Size Diagonal: 66.3 mm

Lens Size Vertical: 44 mm

Lens Thickness: 2.3 mm

Overall Length (lens - tip): 163 mm

Overall Width (hinge - hinge): 136.5 mm

Closest Point Between Lens: 18.5 mm

Strap Length: 420 mm

Materials

Lens: Polycarbonate

Foam: Polycarbonate & Ethylene Vinyl Acetate

Frame: Nylon

Temples: Polycarbonate & Polyvinyl Chloride

Strap: Polyester

Screw: Stainless Steel

Nose Piece: Ethylene Vinyl Acetate

Part No.	Lens Markings	Temple Markings
GB4010STR15	P Z87 + U6	+1.50 P Z87 + / P c SEI Z94.3
GB4010STR20	P Z87 +	+2.00 P Z87 + / P c SEI Z94.3
GB4010STR25	P Z87 +	+2.50 P Z87 + / P c SEI Z94.3

Lens Marking Symbols

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

UV Filter Transmittance

U6: .01% Max Effective Far UV • .1% Max Near UV

Temple Marking Symbols

+1.50: Magnification of +1.5

+2.00: Magnification of +2.0

+2.50: Magnification of +2.5

P: Manufacturer's Mark

Z87: ANSI Standard for Eye and Face Protection Devices

+: High Impact

c SEI Z94.3: CAN/CSA Standard for Eye and Face Protection Devices