

Product data sheet

Characteristics

10287

Multi 9 - comb busbar - 3P - type 3L - 18 mm pitch - 12 modules - 100A

Product availability : Stock - Normally stocked in distribution facility



Main

Range	Multi 9
Product or component type	Comb busbar
Accessory / separate part category	Connection accessory
Poles description	3P
Number of ways	4 ways, type : 3 L (tooth) with 18 mm pitch
Distance between way	2.13 in (54 mm)
Marking	L1 L2 L3
Total number of 18 mm modules	12

Complementary

Insulation	Insulated
Device presentation	Uncuttable
[Ie] rated operational current	100 A (40 °C)
System Voltage	277 V AC Ph/N 480 V AC Ph/Ph
[Ui] rated insulation voltage	690 V AC
[Uimp] rated impulse withstand voltage	12 kV
Mounting mode	Horizontal
Mounting location	Top on tunnel type terminals
9 mm pitches	24
Width	8.5 in (216 mm)
Colour	Light grey (RAL 7035)
Range compatibility	Multi 9 / Multi 9 C60 / C60SP

Environment

Standards	UL 1077 IEC 60947-2
-----------	------------------------

GB 14048.2

Fire resistance	1760 °F (960 °C) (30 s)
-----------------	---------------------------

Ordering and shipping details

Category	00908 - C60N SUPPLEMENTARY PROTECTORS
Discount Schedule	DE2
GTIN	00785901860679
Nbr. of units in pkg.	1
Package weight(Lbs)	0.23999999999999999
Returnability	Y
Country of origin	DE

Offer Sustainability

Sustainable offer status	Not Green Premium product
RoHS (date code: YYWW)	Compliant - since 0726 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations

Contractual warranty

Warranty period	18 months
-----------------	-----------