



**Product Number:** 64973

**Order Abbreviation:** MC150T7.5/DE/830

**General Description:** METALARC POWERBALL 150W ceramic metal halide double ended, clear, universal operation, RSC base, 3000K CCT, high CRI, pulse start, enclosed rated, 15,000 hour rated life

#### Product Information

Abbrev. With Packaging Info.	MC150T7.5DE830 12/CS 1/SKU
ANSI Code 2	C142/E
Approx. Lumens (initial - horizontal)	15000
Approx. Lumens (mean - horizontal)	11840
Arc Length (in)	0.36
Arc Length (mm)	9.2
Base	RX7S
Bulb	MAX 23MM
Color Rendering Index (CRI)	90
Color Temperature/CCT (K)	2950
Diameter (in)	0.906
Diameter (mm)	23.00
Family Brand Name	POWERBALL® CERAMIC METALARC® TUBULAR SINGLE-ENDED
Fixture Requirement	E
Hot Restrike Time (min)	2-15
Light Center Length - LCL (in)	2.6
Light Center Length - LCL (mm)	66
Maximum Base Temperature - Fahrenheit	536
Maximum Bulb Temperature - Fahrenheit	650
Maximum Overall Length - MOL (in)	5.2
Maximum Overall Length - MOL (mm)	132
Nominal Voltage (V)	96.00
Nominal Wattage (W)	150.00
Operating Position	HORIZONTAL +/- 45 DEGREES
Warm-up Time (min)	2-4

#### Footnotes

- Approved electronic ballast is required, view approved ballast list in Product documents, graphs and images.