











HBL500, HBL700 and HBL750 Series

End Fittings	Description	Color	HBL500, HBL700 & HBL750 Series	Description	Color	HBL500, HBL700 & HBL750 Series
	Entrance Connector One ¾ in. KO for panel or conduit connection. One ¾ in. chase nipple and locknut furnished.	Ivory White	HBL5786AIVA HBL5786AWA A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)	Adjustable Offset Connector Two ½ in. KOs for panel or conduit connection. Eliminates offsetting raceway when connecting to surface type panel boxes. One ½ in. chase nipple and locknut furnished.	Ivory White	HBL5786IVA HBL5786WA A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)
	 			 		
	Elbow Box Connector For connecting raceway at right angles to conduit boxes, panel boxes, etc. having ½ in. nipple for trade size conduit.	Ivory White	HBL5783IVA — A: 2.13" (54.05) B: 1.24" (31.50)	Elbow Conduit Connector For connecting raceway at right angles to ½ in. trade size conduit or armored cable connectors.	Ivory White	HBL5784IVA — A: 2.13" (54.05) B: 1.24" (31.50)
	 			 		
	Combination Connector For connecting raceway without offsetting to any 3.25 in. (83.00) or 4 in. (102.00) outlet box mounted on the surface with a KO for ½ in. trade size conduit. Spring steel bushing eliminates need for conduit nipple and locknut.	Ivory White	HBL5785AIVA HBL5785AWA A: 1.50" (38.10) B: 1.84" (46.74) C: 3.89" (98.87)	Corner Box For connecting HBL500, HBL700 or HBL750 Raceway from ceiling or corner. Each leg of base has ½ in. trade size KO.	Ivory White	HBL5719IVA HBL5719WA A: 2.50" (63.50) B: 2.50" (63.50) C: 2.40" (60.96)
	 			 		

Fittings	Description	Color	HBL500 Series	HBL700 Series	HBL750 Series
	Transition Fitting For transitioning from either Wiremold® V500 to Hubbell HBL500 Raceway or Wiremold® V700 to Hubbell HBL700 Raceway or Hubbell HBL750 Raceway.	Ivory White	HBL500TFIV — A: .65" (16.51) B: .89" (22.61) C: 2.15" (54.61)	HBL700TFIV — A: .78" (19.80) B: .89" (22.61) C: 2.15" (54.61)	HBL750TFIV — A: .98" (24.89) B: .89" (22.61) C: 2.15" (54.61)
	 				
	Mounting Strap (one- or two-hole) For mounting HBL500, HBL700 or HBL750 Raceway to surface. Convert to one-hole by breaking off at score.	Ivory White	HBL504IV HBL504W A: .58" (14.73) B: .50" (12.70)	HBL7004IV HBL7004W A: .70" (17.68) B: .50" (12.70)	HBL7504IV HBL7504W A: .90" (22.86) B: .50" (12.70)
	 				
	Connection Cover To cover potential openings where two lengths of like raceways come together.	Ivory White	HBL506IV HBL506W A: .60" (15.24) B: .80" (20.31)	HBL7006IV HBL7006W A: .69" (17.40) B: .80" (20.31)	HBL7506IV HBL7506W A: .91" (23.10) B: .80" (20.31)
	 				
	Bushing Protect wires from potential abrasion. Fits into end of HBL500, HBL700 or HBL750 Raceway.	Steel*	HBL502B A: .35" (8.83) B: .70" (17.68)	HBL7002B A: .49" (12.50) B: .78" (19.80)	HBL7502B A: .60" (15.24) B: .70" (17.68)
	 				

Note: *Zinc Plated Steel.

Wiremold® is a registered trademark of the Wiremold Company.

Dimensions in Inches (mm)