

AFB series boxes are available from our factory as pre-wired assemblies with CONNEXION modular plug-n-play system

SystemOne Recessed 4-Gang Rectangular Floor Boxes, Covers and Plates For Use In Raised Access or Wood Floors

AFB4G50

AFB4G50CHI

57.5 cu. in. (940 cm³)

(2) ½", (4) 1", 1¼", 1½", 2' (4) ½", ¾", 1", 1¼"

.62- 2.12" (15.7- 53.8)

Rectangular

5.37" (136.4)

5.18" (131.4)

11.11" (282.2)

10.90" (276.9)

Rectangular Covers (for use with raised access tiles and wood floors)

Without Insert

4GAFBCVRALU

4GAFBCVRBK

4GAFBCVRBRS

4GAFBCVRBRZ


4GAFBCVRNK

(1) Duplex

FBMPDUP

Opening

(4) ½", ¾", 1", 1¼"



Minimum Depth from Top of Floor Tile

Cubic Inch (cm³) Capacity per Gang

Sides

Bottom

Chicago (No Knockouts)

Dimensions - A

Dimensions - B

Dimensions - C

Floor Thickness

Cover Family

Finish

KO Trade Size: Ends

Temporary Cover Included Note: UL File Number E31999.

UL 514A listed

Aluminum Powder Coat

Black Powder Coat

Brass Powder Coat

Bronze Powder Coat

Satin Nickel Powder Coat





AFB4G25

2.88" (73.2)

2.69" (68.3) 11.11" (282.2)

10.90" (276.9)

(4) ½", ¾", (4) 1", 1¼"

.62- 2.12" (15.7- 53.8)

Rectangular

(4) 1/2", 3/4" (4) 1/2", 3/4"

With Insert

4GAFBCVRALUC

4GAFBCVRBRSC

4GAFBCVRBRZC

4GAFBCVRNKC

4GAFBCVRBKC

AFB4G25CHI

26.5 cu. in. (434.3 cm³)

	1	1
		L
	6	
	Δ	lun









Aluminum Powder Coat				
P		Ч		
	()			



Bronze Powder Coat

Brass Powder Coat

(2) 1U Hubbell

iStation Openings

Note: *Load applied through a 3 in. (76mm) mandrel in center of the cover. Accessories

Description	Catalog Number
AFB4G series replacement dividers.	AFB4GDIVKIT

Plates - for use in 2 and 4-Gang Floor Boxes


Die cast construction available in five finishes

Maximum static load of 1500 lbs. with 2x safety factor*

• UL 51	UL 514A listed				
Plate	(1) Decorator				
Style	Opening				
Cat. No.	FBMPREC				
Plate	(1) 1.5U Hubbe				
Style	iStation Openin				
Cat. No.	FBMP15IM				
Plate	(1) Opening for				







(2) Extron

Openings



Cat. No.	FBMP15IM	FBMP139	FBMP156	FBMPBNK	FBMPFT
Style	iStation Opening	1.40 in. Diameter	1.60 in. Diameter	1-Gang Blank	with Bushing
Plate	(1) 1.5U Hubbell	(1) Simplex Opening	(1) Twist-Lock® Opening		Cable Feed Through
		California in the second of th			

(2) Hubbell Jack Openings and (1) Opening with Hubbell ISF6

(2) Extron[®]

FBMPMAAP

MAAP Openings

Surface Cover Dimensions 13 in. x 131/4 in.












TracJack® or Series II® Style (4) Jack KOs w/Label Field Frame for Keystone Jacks Cat. No. FBMPTRAC FBMP6DJ FBMP6KS







Extron® is a registered trademark of Extron Electronics. Crestron® is a registered trademark of Crestron Electronics, Inc. FSR® is a registered trademark of FSR Inc. TracJack®, Series II® and Ortronics® are registered trademarks of Ortronics/Legrand.

Dimensions in Inches (mm)