



Product Number: 67809

Order Abbreviation: LU250/PLUS/XL/ECO

General Description: 250W High Pressure Sodium lamp, 80,000 hour rated life, noncycling, instant restrike, TCLP, environmentally friendly, ET18, E39 base, universal operation, clear, CCT 2100

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	LU250PLUSXLECO 20/CS 1/SKU
ANSI Code	S50
ANSI Code 2	S50
Approx. Lumens (initial - horizontal)	27500
Approx. Lumens (initial - vertical)	27500
Approx. Lumens (mean - horizontal)	23200
Approx. Lumens (mean - vertical)	23200
Arc Length (in)	2.5
Arc Length (mm)	63.6
Average Rated Life - Horizontal (hr)	80000
Average Rated Life - (hr)	80000
Average Rated Life - Vertical (hr)	80000
Avg Rated Life (hrs)	80000
Base	E39 Mogul
Bulb	ET18
Color Rendering Index (CRI)	22
Color Temperature/CCT (K)	2100
Diameter (in)	2.244
Diameter (mm)	56.99
Family Brand Name	Lumalux PLUS® XL Ecologic®
Fixture Requirement	O
Hot Restrike Time (min)	INSTANT
Lamp Finish	Clear
Light Center Length - LCL (in)	5.75
Light Center Length - LCL (mm)	146
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	9.75
Maximum Overall Length - MOL (mm)	248
Nominal Voltage (V)	100.00
Nominal Wattage (W)	250.00
Operating Position	Universal

Warm-up Time (min)

3-4 MINUTES