## Product data sheet Characteristics

# HOM1224L125PC HOM INDR 125A MLO 12/24CIR

Product availability: Stock - Normally stocked in distribution facility





Price\*: 174.00 USD



#### Main

Product or component type  Range of product  Homeline  Load center type  Main lugs  Line Rated Current  125 A  Number of spaces  12  Number of circuits  24  NEMA degree of protection  NEMA 1 indoor  Cover type  Combination flush/surface cover  Electrical connection  Lugs	IVIAIII	
Load center type Main lugs  Line Rated Current 125 A  Number of spaces 12  Number of circuits 24  NEMA degree of protection NEMA 1 indoor  Cover type Combination flush/surface cover	Product or component type	Load Center
Line Rated Current 125 A  Number of spaces 12  Number of circuits 24  NEMA degree of protection NEMA 1 indoor  Cover type Combination flush/surface cover	Range of product	Homeline
Number of spaces     12       Number of circuits     24       NEMA degree of protection     NEMA 1 indoor       Cover type     Combination flush/surface cover	Load center type	Main lugs
Number of circuits 24  NEMA degree of protection NEMA 1 indoor  Cover type Combination flush/surface cover	Line Rated Current	125 A
NEMA degree of protection  Cover type  Combination flush/surface cover	Number of spaces	12
Cover type Combination flush/surface cover	Number of circuits	24
AL	NEMA degree of protection	NEMA 1 indoor
Electrical connection Lugs	Cover type	Combination flush/surface cover
	Electrical connection	Lugs

### Complementary

-		
Main		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	125 A	
Number of spaces	12	
Number of circuits	24	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Complementary		
Short-circuit current	22 kA	
Number of tandem circuit breakers	12	
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 6AWG 2/0 aluminium	
	AWG 6AWG 1 copper	
Wiring configuration	3-wire	
Material	Tin plated aluminium busbar	
Enclosure material	Welded sheet steel	
Cover finish	Gray baked enamel	
Box number	6	
Environment		
Product certifications	UL E-6294	

#### Environment

Product certifications	UL E-6294			
------------------------	-----------	--	--	--

## Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901876120
Nbr. of units in pkg.	1
Package weight(Lbs)	17.8000000000001
Returnability	Υ
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	