Product data sheet Characteristics

HOM1224L125PGC HOM INDR 125A MLO 12/24CIR WGB

Product availability: Stock - Normally stocked in distribution facility





Price*: 204.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	125 A	
Number of spaces	12	
Number of circuits	24	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	
Provided equipment	Grounding bar [Space(1)	

Complementary

- Complementary	
Short-circuit current	10 kA
Number of tandem circuit breakers	12
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 6AWG 2/0 [Space(aluminium) AWG 6AWG 1 [Space(copper)
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	6

Environment

Dundred neathfreetiens	III E 0004
Product certifications	UL E-6294

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901864776
Nbr. of units in pkg.	1
Package weight(Lbs)	17.5599999999999
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	