Product data sheet Characteristics

HOM12L225PRB HOM OUTD 225A MLO 12CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 423.00 USD



Main

IVIAIII		
Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	225 A	
Number of spaces	12	
Number of circuits	12	
NEMA degree of protection	NEMA 3R outdoor	
Cover type	Surface cover	
Electrical connection	Lugs	

Complementary

Short-circuit current	10 kA	9
Number of tandem circuit breakers	0	<u> </u>
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 4250 kcmil [Space(copper) AWG 4300 kcmil [Space(aluminium)	iffulb
Wiring configuration	3-wire	<u>g</u>
Cover finish	Gray baked enamel	
Material	Tin plated aluminium busbar	
Enclosure material	Welded galvannealed steel	
Surface finish	Baked enamel grey	
Box number	5R	ntario di serio di se

Environment

Product certifications	UL E-6294

Ordering and shipping details

Category	00145 - HOM LC&CVR,12-42CKT NEMA3R
Discount Schedule	DE3C
GTIN	00785901861102
Nbr. of units in pkg.	1
Package weight(Lbs)	26.93
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	