

Product data sheet

Characteristics

HOM1632L225PGC

HOM INDR 225A MLO 16/32 WBG

Product availability : Stock - Normally stocked in distribution facility



Price* : 357.00 USD



Main

Product or component type	Load Center
Range of product	Homeline
Load center type	Main lugs
Line Rated Current	225 A
Number of spaces	16
Number of circuits	32
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs

Complementary

Short-circuit current	10 kA
Number of tandem circuit breakers	16
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 4...250 kcmil [Space(copper) AWG 4...300 kcmil [Space(aluminium)]
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	9

Environment

Product certifications	UL E-6294
------------------------	-----------

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901860976
Nbr. of units in pkg.	1
Package weight(Lbs)	26.150000000000002
Returnability	Y
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Need no specific recycling operations