Product data sheet Characteristics

HOM2040L125PC HOM INDR 125A MLO 20/40CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 237.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	125 A	
Number of spaces	20	
Number of circuits	40	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	

Complementary

		_
Short-circuit current	10 kA	
Number of tandem circuit breakers	20	
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 6AWG 2/0 aluminium AWG 6AWG 1 copper	tiinte for
Wiring configuration	3-wire	
Material	Tin plated aluminium busbar	
Enclosure material	Welded sheet steel	
Cover finish	Gray baked enamel	
Box number	8	

Environment

Product certifications	UL E-6294		
------------------------	-----------	--	--

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901860693
Nbr. of units in pkg.	1
Package weight(Lbs)	24.10000000000001
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	