

Product availability : Stock - Normally stocked in distribution facility



Price* : 288.00 USD



Main

| | |
|---------------------------|---------------------------------|
| Product or component type | Load Center |
| Range of product | Homeline |
| Load center type | Main lugs |
| Line Rated Current | 125 A |
| Number of spaces | 20 |
| Number of circuits | 40 |
| NEMA degree of protection | NEMA 1 indoor |
| Cover type | Combination flush/surface cover |
| Electrical connection | Lugs |
| Provided equipment | Grounding bar [Space(1)] |

Complementary

| | |
|-----------------------------------|---|
| Short-circuit current | 10 kA |
| Number of tandem circuit breakers | 20 |
| Phase | 1 phase |
| System Voltage | 120/240 V AC |
| AWG gauge | AWG 6...AWG 2/0 [Space(aluminium)] AWG 6...AWG 1/0 [Space(copper)] |
| Wiring configuration | 3-wire |
| Cover finish | Gray baked enamel |
| Material | Tin plated aluminium busbar |
| Enclosure material | Welded sheet steel |
| Surface finish | Baked enamel grey |
| Box number | 8 |

Environment

| | |
|------------------------|-----------|
| Product certifications | UL E-6294 |
|------------------------|-----------|

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 00045 - HOM LC&CVR,12-42 CKT,NEMA1 |
| Discount Schedule | DE3C |
| GTIN | 00785901848523 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 23.670000000000002 |
| Returnability | Y |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1414 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |