## Product data sheet Characteristics

# HOM2040L225PGC HOM INDR 225A MLO 20/40CIR WGB

Product availability: Stock - Normally stocked in distribution facility





Price\*: 417.00 USD





#### Main

TTT COLL		Č
Product or component type	Load Center	to to
Range of product	Homeline	
Load center type	Main lugs	ase n
Line Rated Current	225 A	ċ t
Number of spaces	20	S III
Number of circuits	40	 relia
NEMA degree of protection	NEMA 1 indoor	2
Cover type	Combination flush/surface cover	ultan
Electrical connection	Lugs	ning
Provided equipment	Grounding bar [Space(1)	etermi

#### Complementary

Short-circuit current	10 kA	
Number of tandem circuit breakers	20	
Phase	1 phase	
System Voltage	120/240 V AC	
AWG gauge	AWG 4250 kcmil copper AWG 4300 kcmil aluminium	
Wiring configuration	3-wire	
Material	Tin plated aluminium busbar	
Enclosure material	Welded sheet steel	
Cover finish	Gray baked enamel	
Box number	9	

#### Environment

Product certifications	UL E-6294

## Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1
Discount Schedule	DE3C
GTIN	00785901861126
Nbr. of units in pkg.	1
Package weight(Lbs)	26.34
Returnability	Υ
Country of origin	US

### Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	