Product data sheet Characteristics

HOM3060L225PC HOM INDR 225A MLO 30/60CIR

Product availability: Stock - Normally stocked in distribution facility





Price*: 420.00 USD



Main

Product or component type	Load Center	
Range of product	Homeline	
Load center type	Main lugs	
Line Rated Current	225 A	
Number of spaces	30	
Number of circuits	60	
NEMA degree of protection	NEMA 1 indoor	
Cover type	Combination flush/surface cover	
Electrical connection	Lugs	

Complementary

Short-circuit current	10 kA	9
Number of tandem circuit breakers	30	
Phase	1 phase	not
System Voltage	120/240 V AC	pue
AWG gauge	AWG 4250 kcmil copper AWG 4300 kcmil aluminium	titute for
Wiring configuration	3-wire	
Material	Tin plated aluminium busbar	
Enclosure material	Welded sheet steel	
Cover finish	Gray baked enamel	itri
Box number	10	

Environment

Product certifications	UL E-6294			
------------------------	-----------	--	--	--

Ordering and shipping details

Category	00045 - HOM LC&CVR,12-42 CKT,NEMA1		
Discount Schedule	DE3C		
GTIN	00785901977209		
Nbr. of units in pkg.	1		
Package weight(Lbs)	29.59		
Returnability	Υ		
Country of origin	US		

Offer Sustainability

Sustainable offer status	Green Premium product	
RoHS (date code: YYWW)	Compliant - since 1414 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product environmental profile	Available	
Product end of life instructions	Need no specific recycling operations	