



Main

Product or component type	Load Center
Range of product	Homeline
Load center type	Main lugs
Line Rated Current	225 A
Number of spaces	30
Number of circuits	60
NEMA degree of protection	NEMA 1 indoor
Cover type	Combination flush/surface cover
Electrical connection	Lugs
Provided equipment	Grounding bar (1) Circuit breaker (3) 1P 20 A 120/240 V AC Circuit breaker (2) 2P 30 A 120/240 V AC

Complementary

Short-circuit current	10 kA
Number of tandem circuit breakers	30
Phase	1 phase
System Voltage	120/240 V AC
AWG gauge	AWG 4...300 kcmil (aluminium) AWG 4...250 kcmil (copper)
Wiring configuration	3-wire
Cover finish	Gray baked enamel
Material	Tin plated aluminium busbar
Enclosure material	Welded sheet steel
Surface finish	Baked enamel grey
Box number	10

Environment

product certifications	UL E-6294
------------------------	-----------

Offer Sustainability

Green Premium product	Green Premium product
Compliant - since 1414 - Schneider Electric declaration of conformity	Compliant - since 1414 - Schneider Electric declaration of conformity
Reference not containing SVHC above the threshold	Reference not containing SVHC above the threshold
Available	Available
Need no specific recycling operations	Need no specific recycling operations

The information provided in this documentation contains general descriptions and/or technical characteristics of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.