

Product data sheet

Characteristics

HOM3060L225PRB

HOM OUTD 225A MLO 30/60CIR

Product availability : Stock - Normally stocked in distribution facility



Price* : 587.00 USD



Main

| | |
|---------------------------|-----------------|
| Product or component type | Load Center |
| Range of product | Homeline |
| Load center type | Main lugs |
| Line Rated Current | 225 A |
| Number of spaces | 30 |
| Number of circuits | 60 |
| NEMA degree of protection | NEMA 3R outdoor |
| Cover type | Surface cover |
| Electrical connection | Lugs |

Complementary

| | |
|-----------------------------------|---|
| Short-circuit current | 10 kA |
| Number of tandem circuit breakers | 30 |
| Phase | 1 phase |
| System Voltage | 120/240 V AC |
| AWG gauge | AWG 4...250 kcmil copper AWG 4...300 kcmil aluminium |
| Wiring configuration | 3-wire |
| Material | Tin plated aluminium busbar |
| Enclosure material | Welded galvanized steel |
| Cover finish | Gray baked enamel |
| Box number | 7R |

Environment

| | |
|------------------------|-----------|
| Product certifications | UL E-6294 |
|------------------------|-----------|

Ordering and shipping details

| | |
|-----------------------|------------------------------------|
| Category | 00145 - HOM LC&CVR,12-42CKT NEMA3R |
| Discount Schedule | DE3C |
| GTIN | 00785901977490 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 36.899999999999999 |
| Returnability | Y |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------------|---|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 1414 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |