

---

## 20A, 3° 480V TURNLOK® WATERTIGHT CONNECTOR, NEMA 4X/6P, YELLOW

27W76 | [Pass & Seymour](#)



---

### FEATURES & BENEFITS

Rated watertight for 1,500 psi high-pressure hosedown, P&S Turnlok® watertight plugs & connectors feature rugged construction, multiple seals to ensure protection against the environment and ease of installation.

- Thermoplastic elastomer (TPV) construction stands up to impacts, oils, chemicals, heat and weather.
- Nickel-plated blades and contacts for long-lasting, superior corrosion resistance.
- Multi-point sealing system provides environmental protection of NEMA 4, 4X, 6, 6P, & IP67 rated.
- Devices resist high-pressure hosedown of 1,500 psi.
- Color-coded sealing bushings provided for large range of cord diameters
- Large ribs on body for a superior grip when mating.
- For Covering Patents, see [www.legrand.us/patents](http://www.legrand.us/patents).

---

### SPECIFICATIONS

#### GENERAL INFO

Color: Yellow

Type: Connector

Features: Watertight

Number Of Poles: 3

Number Of Wires: 4

Special Features: Watertight

#### LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

CSA Listing Info: C22.2 No. 42

CSA Standard: Yes

UL Listing No: UL498 (Plug/Connector)

UL Standard: Yes

#### CONSTRUCTION INFORMATION

Material 1: Rubber

#### DIMENSIONS

Diameter (US): 2.53"

Length (US): 4.88"

#### TECHNICAL INFORMATION

Amps: 20A

Material: Rubber

NEMA Configuration Number: L16-20R

NEMA Rating: 4X/6P

Volts: 3° 480V

#### BUY AMERICAN ACT COMPLIANCE

Country Of Origin: UNITED STATES OF AMERICA

Buy American Act Status: Buy American Act Compliant

