

Product availability : Stock - Normally stocked in distribution facility



Main

Product or component type	Miniature circuit-breaker
Range of product	QO
Line Rated Current	20 A
System Voltage	208Y/120 V AC
Mounting mode	Bolt-on
Poles description	3P
Circuit breaker type	Ground fault protecting class A 6 mA
Circuit breaker application	Not rated
Electrical connection	Box lugs

Complementary

Breaking capacity	10 kA at: 208Y/120 V AC
Number of spaces required	3
AWG gauge	AWG 12...AWG 4 (aluminium) AWG 14...AWG 6 (copper)
Height	4.12 in
Depth	2.91 in
Width	2.25 in

Environment

Product certifications	UL listed CSA
Ambient air temperature for operation	104 °F (40 °C)

Ordering and shipping details

Category	00103 - QO 2 POLE GFI CB 40-60A
----------	---------------------------------

Discount Schedule	DE2A
GTIN	00785901732228
Nbr. of units in pkg.	1
Package weight(Lbs)	1.3900000000000001
Returnability	Y
Country of origin	MX

Offer Sustainability

Sustainable offer status	Green Premium product
RoHS (date code: YYWW)	Compliant - since 1340 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity
REACH	Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold
Product environmental profile	Available
Product end of life instructions	Available

Contractual warranty

Warranty period	18 months
-----------------	-----------