Product data sheet Characteristics

QO124L125PGRB QO PLUG-ON NEUT LC N3R 1 PH ML 240V 125A

Product availability: Stock - Normally stocked in distribution facility



Price*: 712.00 USD



Main

Widin		
Product or component type	Load Center	
Range of product	QO	
Load center type	Main lugs	
Line Rated Current	125 A	
Number of spaces	24	
Short-circuit current	65 kA	
Number of circuits	24	
Number of tandem circuit breakers	0	
Phase	1 phase	

Complementary

AWG gauge	AWG 6AWG 2/0 (aluminium/copper)	
NEMA degree of protection	NEMA 3R outdoor	. <u>v</u>
Cover type	Surface cover	
Device composition	Grounding bar included (not installed)	₹
Electrical connection	Lugs	
Wiring configuration	3-wire	
Material	Tin plated copper busbar	
Enclosure material	Welded galvannealed steel	
Surface finish	Baked enamel grey	
Box number	4R	. <u>.</u>
Product certifications	UL listed	
Height	22.05 in (560 mm)	
Width	14.76 in (375 mm)	

Ordering and shipping details

Category	10002 - QO PON 1PH LC,12-60 CKT, N3R
Discount Schedule	DE3A
GTIN	00785901101383
Nbr. of units in pkg.	1
Package weight(Lbs)	24.2899999999999
Returnability	Υ
Country of origin	US

Offer Sustainability

Sustainable offer status	Not Green Premium product	-
RoHS (date code: YYWW)	Compliant - since 1248 - Schneider Electric declaration of conformity	
	Schneider Electric declaration of conformity	
REACh	Reference not containing SVHC above the threshold	
	Reference not containing SVHC above the threshold	
Product end of life instructions	Need no specific recycling operations	