




# 2 and 4-Gang Rectangular Floor Boxes

## SystemOne Recessed 2-Gang Rectangular Floor Boxes, Covers and Plates For Use In Raised Access or Wood Floors

**ScrubShield**   
Complies with UL514A


Style			
<b>Box Type</b>		<b>AFB2G50</b> <b>AFB2G50CHI</b>	<b>AFB2G25</b> <b>AFB2G25CHI</b>
Standard Chicago (No Knockouts)			
Minimum Depth from Top of Floor Tile		5.32" (135.1)	2.88" (73.2)
Cubic Inch (cm <sup>3</sup> ) Capacity per Gang		60 cu. in. (980 cm <sup>3</sup> )	30 cu. in. (491.7 cm <sup>3</sup> )
Furniture Feed; Cubic Inch (cm <sup>3</sup> ) Capacity per Chamber		135 cu. in. (2212.2 cm <sup>3</sup> )	78 cu. in. (1288.3 cm <sup>3</sup> )
Dimensions – A		5.12" (130.1)	2.68" (68.2)
Dimensions – B		6.32" (160.5)	6.32" (160.5)
Dimensions – C		12.82" (325.6)	12.82" (325.6)
KO Trade Size: Ends		(2) 1/2", (2) 1", 1-1/4", 1-1/2", 2"	(4) 1/2", 3/4"
Sides		(4) 1/2", 3/4", 1", 1-1/4"	(4) 1/2", 3/4"
Bottom		(4) 1/2", 3/4", 1", 1-1/4"	(2) 1/2", 3/4", (2) 1", 1-1/4"
Floor Thickness		.62- 2.12" (15.7- 53.8)	.62- 2.12" (15.7- 53.8)
Cover Family		Rectangular	Rectangular
Temporary Cover Included		✓	✓




Aluminum Powder Coat



Black Powder Coat



Bronze Powder Coat



Brass Powder Coat

Note: UL File Number E31999.

### Rectangular Covers (for use with raised access tiles and wood floors)

- Die cast construction available in five finishes
- Furniture feed includes one 2 in. conduit hub and one 1 in. conduit hub with reducer to 3/4 in.
- Maximum static load of 800 lbs. with 2x safety factor\*
- Furniture Feed Covers ship with low voltage dividers

Surface Cover Dimensions 15 in. x 8-3/4 in.

Finish	Without Insert	With Insert	Furniture Feed
Aluminum Powder Coat	<b>2GAFBCVRALU</b>	<b>2GAFBCVRALUC</b>	<b>2GAFBFFCVRALU</b>
Black Powder Coat	<b>2GAFBCVRBK</b>	<b>2GAFBCVRBKC</b>	<b>2GAFBFFCVRBK</b>
Brass Powder Coat	<b>2GAFBCVRBRS</b>	<b>2GAFBCVRBRSC</b>	<b>2GAFBFFCVRBRS</b>
Bronze Powder Coat	<b>2GAFBCVRBRZ</b>	<b>2GAFBCVRBRZC</b>	<b>2GAFBFFCVRBRZ</b>
Satin Nickel Powder Coat	<b>2GAFBCVRNK</b>	<b>2GAFBCVRNKC</b>	<b>2GAFBFFCVRNK</b>

Note: \*Load applied through a 3 in. (76mm) mandrel in center of the cover.

### Plates - for use in 2 and 4-Gang Floor Boxes

UL 514A Listed

Plate Style	(1) Decorator Opening	(1) Duplex Opening	(2) Extron <sup>®</sup> MAAP Openings	(2) Extron Openings	(2) 1U Hubbell iStation Openings
Cat. No.	<b>FBMPREC</b>	<b>FBMPDUP</b>	<b>FBMPMAAP</b>	<b>FBMPAAP</b>	<b>FBMP2IM</b>
Plate Style	(1) 1.5U Hubbell iStation Opening	(1) Simplex Opening 1.40 in. Diameter	(1) Twist-Lock <sup>®</sup> Opening 1.60 in. Diameter	1-Gang Blank	Cable Feed Through with Bushing
Cat. No.	<b>FBMP15IM</b>	<b>FBMP139</b>	<b>FBMP156</b>	<b>FBMPBNK</b>	<b>FBMPFT</b>
Plate Style	(1) Opening for TracJack <sup>®</sup> or Series II <sup>®</sup>	(2) Hubbell Jack Openings and (4) Jack KOs w/Label Field	(1) Opening with Hubbell ISF6 Frame for Keystone Jacks		
Cat. No.	<b>FBMPTRAC</b>	<b>FBMP6DJ</b>	<b>FBMP6KS</b>		

Extron<sup>®</sup> is a registered trademark of Extron Electronics. Crestron<sup>®</sup> is a registered trademark of Crestron Electronics, Inc. FSR<sup>®</sup> is a registered trademark of FSR Inc. TracJack<sup>®</sup>, Series II<sup>®</sup> and Ortronics<sup>®</sup> are registered trademarks of Ortronics/Legrand.

Dimensions in Inches (mm)