ScrubShield[®] c (UL) us Complies with UL514A

SystemOne Recessed 2-Gang Floor Boxes and Covers, for Use In Concrete Floors

Style	Rectangu	ar Cover	Round Cover		
E B B B C C C C C C C C C C C C C C C C		1.10		1.010	
Standard Box Corrosion-Resistant (On-grade)	CFB2G30E CFB2G30CRE	CFB2G25E CFB2G25CRE	CFB2G30RE CFB2G30RCRE	CFB2G25RE CFB2G25RCRE	
Recommended Pour Depth	3.50" (88.9)	3.00" (76.2)	3.75" (95.3)	3.25" (82.6)	
Min. Depth of Pour	3.00" (76.2)	2.50" (63.5)	3.75" (95.3)	3.25" (82.6)	
Adjustability	Fully	Fully	Fully	Fully	
Cubic Inch (cm3) Capacity per Gang	56.5 cu. in. (926 cm ³)	47.5 cu. in. (778 cm ³)	56.5 cu. in. (926 cm ³)	47.5 cu. in. (778 cm ³)	
Dimensions – A	3.00" (76.2)	2.50" (63.5)	_	-	
Dimensions – B	6.62" (168.1)	6.62" (168.1)	7.32" (185.9)	7.32" (185.9)	
Dimensions – C	16.27" (413.3)	16.27" (413.3)	16.27" (413.3)	16.27" (413.3)	
Dimensions – D	-	-	6.37" (161.7) TYP.	6.37" (161.7) TYP.	
Dimensions – E	3.50" (88.9)	3.00" (76.2)	3.75" (95.3)	3.25" (82.6)	
KO Trade Size: Ends Sides Bottom	(2) $\frac{1}{2^{"}}, \frac{9}{4^{"}}, 1^{"}, 1\frac{1}{4^{"}}$ (4) $\frac{3}{4^{"}}, 1^{"}, 1\frac{1}{4^{"}}, 2^{"*}$ (4) $\frac{1}{2^{"}}, \frac{9}{4^{"}}, 1^{"}, 1\frac{1}{4^{"}}$	$\begin{array}{c} (2) \ 1\!\!/\!2^{\texttt{u}}, \ 9\!\!/\!4^{\texttt{u}}, \ 1^{\texttt{u}} \\ (4) \ 1\!\!/\!2^{\texttt{u}}, \ 9\!\!/\!4^{\texttt{u}}, \ 1^{\texttt{u}} \\ (4) \ 1\!\!/\!2^{\texttt{u}}, \ 9\!\!/\!4^{\texttt{u}}, \ (4) \ 1^{\texttt{u}}, \ 11\!\!/\!4^{\texttt{u}} \end{array}$	$\begin{array}{c} (2) \ \frac{1}{2^{u}}, \ \frac{3}{4^{u}}, \ 1^{u}, \ 1\frac{1}{4^{u}} \\ (4) \ \frac{3}{4^{u}}, \ 1^{u}, \ 1\frac{1}{4^{u}}, \ 2^{u*} \\ (4) \ \frac{1}{2^{u}}, \ \frac{3}{4^{u}}, \ 1^{u}, \ 1\frac{1}{4^{u}} \end{array}$	(2) 1/2", 3/4", 1" (4) 1/2", 3/4", 1" (4) 1/2", 3/4", 1", 11/4"	
Cover Style	Rectangular	Rectangular	Round	Round	
2 Inch Hub Compatible	Yes	No	Yes	No	

Note: UL File Number E31999. Boxes include concrete covers.

*Requires CFBHUB2 for 2" conduits. CFBHUB200PVC for 2" PVC conduits or CFBHUB125PVC for 11/4" PVC condits.

Rectangular Covers

٠

- Compatible with CFB2G25, CFB2G25CR, CFB2G30 and CFB2G30CR Series Floor Boxes
- Surface style typical applications: Carpet, VCT
- Flush style typical applications: Tile, finished concrete and Terrazzo floors
- Two large cable egress doors and access 180° opening Maximum static load of 800 lbs, with 2x safety factor*
- Eurniture Feed covers ship with low voltage dividers

 Maximum static load 	a of 800 ids. with 2	x salely lactor	Furniture F	-eed covers snip v	vith low voltage divi	ders
Surface Cover Dimensions 11			₆ in. x 7 ³ / ₁₆ in.	Flush Cover Dimensions $10^{11}/_{16}$ in. x $6^{3}/_{16}$ in.		
Finish	Without Insert	With Insert	Furniture Feed (1 in. and 2 in. Plugs)	Without Insert	With Insert	Furniture Feed (1 in. and 2 in. Plugs)
Aluminum Powder Coat Black Powder Coat Brass Powder Coat Bronze Powder Coat Satin Nickel Powder Coat	24GCCVRALU 24GCCVRBK 24GCCVRBRS 24GCCVRBRZ 24GCCVRNK	24GCCVRALUC 24GCCVRBKC 24GCCVRBRSC 24GCCVRBRZC 24GCCVRNKC	24GCFFCVRALU 24GCFFCVRBK 24GCFFCVRBRS 24GCFFCVRBRZ 24GCFFCVRNK	24GTCVRALU 24GTCVRBK 24GTCVRBRS 24GTCVRBRZ 24GTCVRNK	24GTCVRALUC 24GTCVRBKC 24GTCVRBRSC 24GTCVRBRZC 24GTCVRNKC	24GTFFCVRALU 24GTFFCVRBK 24GTFFCVRBRS 24GTFFCVRBRZ 24GTFFCVRNK
	Aluminum Powder Coat	Black Powder Coat	Brass Powder Coat	Bronze Powder Coat	Satin Nickel Powder Coat	Aluminum Powder Coat
6 Inch Round Cove	rs					
 Compatible with CFE CFB2G30RCR Series Cover flanges have a 	Floor Boxes		Recessed	covers- 180° acc	0 lbs. with 2x safe ess with 2 cable eq vith low voltage div	gress doors
Finish Flush Surface		Furniture Feed (¾ in. and 2 in. Plugs)				
Brushed Aluminum Black Powder Coat Brass Plated	CFBS1	R6CVRALU R6CVRBLK R6CVRBRS	CFBS1R6FFC CFBS1R6FFC CFBS1R6FFC	VRBLK		

CFBS1R6FFCVRBRZ

CFBS1R6FFCVRGRY

CFBS1R6FFCVRNKL

CFBS1R6CVRBRZ

CFBS1R6CVRGRY

CFBS1R6CVRNKL

Dimensions in Inches (mm)

Antique Bronze Plated

Gray Powder Coat

Satin Nickel Plated

Note: *Load applied through a 3 in. (76mm) mandrel in center of the cover. See page P5 for round cover finishes.