

## 15 Amp, 125 Volts 2 Pole, 2 Wire, Non-Grounding

IP20  
SUITABILITY15A 125V  
NEMA L1-15P  
0.5 HP

HBL7545C

### Plugs

Description	Cord Dia.	Catalog Number
Black and white nylon, polarized. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7545C

Note: See page C-51 for accessories.

### Flanged Inlets

Description	Catalog Number
Nylon casing, polarized, backwired, Multiple drive screws.	HBL7524C

Note: See page C-50 for accessories.

### Connector Bodies

Description	Cord Dia.	Catalog Number
Black and white nylon. Multiple drive screws.	.230"-.720" (5.8-18.3)	HBL7506C

Note: See page C-51 for accessories.

### Receptacles


Description	Catalog Number
Duplex, flush, black phenolic.	HBL7540
Single, flush, black phenolic.	HBL7535
Single, panel mount, 1-15/16" (49.2) centers, black phenolic.	HBL7498

Note: See page C-50 for accessories.


### Flanged Receptacles

Description	Catalog Number
Insulgrip nylon casing, backwired. Multiple drive screws.	HBL7526C
Metal flange, stainless steel casing, black phenolic, exposed terminals.	HBL7526

Note: See pages C-50 and C-51 for accessories.

Only receptacles and plugs are HP rated.  
HP ratings are AC only.

HBL7540



HBL7526C

HBL7498

HBL7535

Dimensions in Inches (mm)