



**Product Number:** 64054

**Order Abbreviation:** M400/PS/U/ED37

**General Description:** 400W METALARC PULSE START metal halide lamp, reduced color shift, E39 base, ED37 bulb, enclosed fixture rated, universal burn, clear, 4000K

**\* Full Case Required**

#### Product Information

Abbrev. With Packaging Info.	M400PSUED37 6/CS 1/SKU
ANSI Code	M155/E
ANSI Code 2	M155/S
Approx. Lumens (initial - horizontal)	31000
Approx. Lumens (initial - vertical)	36000
Approx. Lumens (mean - horizontal)	22400
Approx. Lumens (mean - vertical)	25500
Arc Length (in)	1.5
Arc Length (mm)	38
Average Rated Life - Horizontal (hr)	15000
Average Rated Life - (hr)	15000
Average Rated Life - Vertical (hr)	20000
Base	E39 Mogul
Bulb	ED37
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4000
Family Brand Name	Metalarc® Pulse Start
Fixture Requirement	E
Hot Restrike Time (min)	5-7
Lamp Finish	Clear
Light Center Length - LCL (in)	7
Light Center Length - LCL (mm)	178
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	11.5
Maximum Overall Length - MOL (mm)	292
Nominal Wattage (W)	400.00
Operating Position	UNIVERSAL
Warm-up Time (min)	2-4