



Product Number: 64043

Order Abbreviation: M175/PS/U/ED28

General Description: 175W METALARC PULSE START metal halide lamp, reduced color shift, E39 base, ED28 bulb, enclosed fixture rated, universal burn, clear, 4000K

*** Full Case Required**

Product Information

Abbrev. With Packaging Info.	M175PSUED28 6/CS 1/SKU
ANSI Code	M152/E
ANSI Code 2	M152/E
Approx. Lumens (initial - horizontal)	13500
Approx. Lumens (initial - horizontal) 2	12150
Approx. Lumens (initial - vertical)	14
Approx. Lumens (mean - horizontal)	8
Approx. Lumens (mean - vertical)	10
Arc Length (in)	1.02
Arc Length (mm)	26
Average Rated Life - Horizontal (hr)	9000
Average Rated Life - (hr)	9000
Average Rated Life - Vertical (hr)	12000
Base	E39 Mogul
Bulb	ED28
Color Rendering Index (CRI)	65
Color Temperature/CCT (K)	4500
Diameter (in)	3.504
Diameter (mm)	89
Family Brand Name	Metalarc® Pulse Start
Fixture Requirement	E
Hot Restrike Time (min)	4 - 7
Lamp Finish	Clear
Light Center Length - LCL (in)	5
Light Center Length - LCL (mm)	127
Maximum Base Temperature - Fahrenheit	482
Maximum Base Temperature - Celsius	250
Maximum Bulb Temperature - Fahrenheit	752
Maximum Bulb Temperature - Celsius	400
Maximum Overall Length - MOL (in)	8.31
Maximum Overall Length - MOL (mm)	211
Nominal Wattage (W)	175.00
Operating Position	Universal
Warm-up Time (min)	2 - 4

