

# H362AWAVW

Safety switch, heavy duty, fusible, 60A,  
600 VAC/VDC, 3 poles, 50 hp, NEMA 12K,  
appleton, view window



## Main

Product	Receptacle Switch
For Use With	Plug ACP6034BC Appleton Powertite
Current Rating	60 A
Enclosure Rating	NEMA 3R/12 galvanized steel
Horsepower Rating	15 Hp 480 V AC 50...60 Hz 3 phase NEC 240.6 30 Hp 480 V AC 50...60 Hz 3 phase NEC 430.52 15 Hp 600 V AC 50...60 Hz 3 phase NEC 240.6 50 Hp 600 V AC 50...60 Hz 3 phase NEC 430.52 10 hp at 250 V DC conforming to NEC 240.6
Disconnect Type	Fusible disconnect switch
Mounting Type	Surface
Number of Poles	3
Phase	3 phase
Electrical Connection	Receptacle
Certifications	UL Listed
Voltage Rating	600 V AC 250 V DC
Wire Size	AWG 12...AWG 2 aluminium AWG 14...AWG 2 copper
Wire Configuration	4-wire Without neutral

## Complementary

Width	10.5 in (266.70 mm)
Height	16.5 in (419.10 mm)
Maximum Depth	7 in (177.80 mm)

## Ordering and shipping details

Category	00124 - H&HU SW,W/APPLETON RECPT - WA
Discount Schedule	DE1
GTIN	00785901351924
Nbr. of units in pkg.	1
Package weight(Lbs)	17 lb(US) (7.71 kg)
Returnability	Yes
Country of origin	US

## Offer Sustainability

Sustainable offer status	Green Premium product
California proposition 65	WARNING: This product can expose you to chemicals including: Lead and lead compounds, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to <a href="http://www.P65Warnings.ca.gov">www.P65Warnings.ca.gov</a>
RECh Regulation	RECh Declaration
RECh free of SVHC	Yes
EU RoHS Directive	Compliant  EU RoHS Declaration
Mercury free	Yes

The information provided in this documentation contains general descriptions and/or technical characteristics of the performance of the products contained herein. This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications. It is the duty of any such user or integrator to perform the appropriate and complete risk analysis, evaluation and testing of the products with respect to the relevant specific application or use thereof. Neither Schneider Electric Industries SAS nor any of its affiliates or subsidiaries shall be responsible or liable for misuse of the information contained herein.

RoHS exemption information	<a href="#">Yes</a>
China RoHS Regulation	<a href="#">China RoHS Declaration</a>
Environmental Disclosure	<a href="#">Product Environmental Profile</a>
PVC free	Yes

### Contractual warranty

Warranty	18 months
----------	-----------