Product data sheet Characteristics

QOB235

QO Miniature Circuit Breaker 35A 2P 120/240V 10kA Bolt-on Mount

Product availability: Stock - Normally stocked in distribution facility





Price*: 89.00 USD



Main

| 0 20 20 | | |
|--|--|----------|
| 1 | | |
| - | | |
| | | |
| Main | | |
| Product or component type | Miniature circuit-breaker | |
| Range of product | QO | |
| Line Rated Current | 35 A | |
| System Voltage | 120/240 V AC 48 V DC | |
| Mounting mode | Bolt-on | |
| Poles description | 2P | |
| Circuit breaker type | Standard | |
| Circuit breaker application | HACR rated | |
| Electrical connection | Box lugs | |
| | | |
| | | |
| Complementary Breaking capacity | 10 kA at: 120/240 V AC 5 kA at: 48 V DC | <u> </u> |
| | | |
| Breaking capacity Number of spaces required | 5 kA at: 48 V DC | |
| Breaking capacity Number of spaces required AWG gauge | 5 kA at: 48 V DC 2 | |
| Breaking capacity Number of spaces required AWG gauge Environment | 5 kA at: 48 V DC 2 AWG 8AWG 2 (copper or aluminium) | |
| Breaking capacity Number of spaces required AWG gauge Environment | 5 kA at: 48 V DC 2 | |
| Breaking capacity Number of spaces required AWG gauge Environment Product certifications | 5 kA at: 48 V DC 2 AWG 8AWG 2 (copper or aluminium) UL listed | |
| Breaking capacity Number of spaces required | 5 kA at: 48 V DC 2 AWG 8AWG 2 (copper or aluminium) UL listed CSA | |
| Breaking capacity Number of spaces required AWG gauge Environment Product certifications Ambient air temperature for operation | 5 kA at: 48 V DC 2 AWG 8AWG 2 (copper or aluminium) UL listed CSA 104 °F (40 °C) | |
| Breaking capacity Number of spaces required AWG gauge Environment Product certifications Ambient air temperature for operation Ordering and shipping details | 5 kA at: 48 V DC 2 AWG 8AWG 2 (copper or aluminium) UL listed CSA | |
| Breaking capacity Number of spaces required AWG gauge Environment Product certifications | 5 kA at: 48 V DC 2 AWG 8AWG 2 (copper or aluminium) UL listed CSA 104 °F (40 °C) | |

Complementary

| Breaking capacity | 10 kA at: 120/240 V AC 5 kA at: 48 V DC |
|---------------------------|--|
| Number of spaces required | 2 |
| AWG gauge | AWG 8AWG 2 (copper or aluminium) |

Environment

| Product certifications | UL listed CSA |
|---------------------------------------|------------------|
| | OUA |
| Ambient air temperature for operation | 104 °F (40 °C) |

Ordering and shipping details

| Category | 00015 - QOB CIRCUIT BREAKERS |
|-------------------|------------------------------|
| Discount Schedule | DE2 |
| GTIN | 00785901368298 |

| Nbr. of units in pkg. | 1 |
|-----------------------|-----------------|
| Package weight(Lbs) | 0.5999999999998 |
| Returnability | Υ |
| Country of origin | MX |

Offer Sustainability

| Sustainable offer status | Green Premium product |
|----------------------------------|---|
| RoHS (date code: YYWW) | Compliant - since 1323 - Schneider Electric declaration of conformity |
| | Schneider Electric declaration of conformity |
| REACh | Reference not containing SVHC above the threshold |
| | Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |
| | |

Contractual warranty

| Warranty period | 18 months |
|-----------------|-----------|