



UPC Code: 07847765533
Country Of Origin: Mexico

Ivory

Color:

TCR20-I

Brand Features

Plug Into Safety with Leviton Tamper-Resistant (TR) Receptacles. As a long-time manufacturer of tamper-resistant devices, we are pleased to be at the forefront of this safety measure with an expanded product line that encompasses a wide range of TR devices in Residential, Commercial, Industrial and Hospital Grades.

The National Electrical Code® mandates the use of tamper-resistant receptacles in various applications, and has expanded the usage requirements over the course of several code cycles. To see which version of the National Electrical Code your State or Locality has adopted, please click here.

Item Description

Duplex Receptacle Outlet, Commercial Specification Grade, Tamper-Resistant, Smooth Face, 20 Amp, 125 Volt, Side Wire, NEMA 5-20R, 2-Pole, 3-Wire, Self-Grounding - Ivory

Technical Information

AC Horsepower Ratings
Horsepower Rating: 1 HP
Electrical Specifications

Amperage: 20 A

Current Limiting: Full Rated Current **Dielectric Voltage:** Withstands 2000V

per UL498

Grounding: Self-Grounding

Pole: 2

Temperature Rise: Max 30C after 100 cycles OL at 150 percent rated current

Voltage: 125 VAC

Wire: 3

Environmental Specifications

Flammability: Rated V-2 per UL94

Operating Temperature: -40°C to 60°C

Material Specifications **Body Material:** Thermoplastic

Face Material: Thermoplastic

Ground Clips: Brass

Grounding Screw: Plated Steel Line Contacts: Brass .031 Thick Shutter Mechanism: Delrin® Acetal Strap Material: Zinc-Plated Steel Terminal Screws: Plated Steel Mechanical Specifications

Product ID: Ratings are permanently marked on device

marked on device

Terminal Accom.: 10-14 AWG

Terminal ID: Brass-Hot, Green-Ground,

Silver-Neutral

Termination: Side Wire

Wire Type: Solid or Stranded Building

Wire

Product Features
Color: Ivory

Device Type: Duplex Receptacle Outlet

Feature 2: Tamper-Resistant
Feature 4: Smooth Face

Grade: Commercial Specification Grade

Standards and Certifications

ANSI: C-73

cULus: File E13399 NEMA: WD-1 & WD-6

NOM: 057 Warranty

Warranty: 10-Year Limited

SPECIFICATION SUBMITTAL

JOB NAME:	CATALOG NUMBERS:	
JOB NUMBER:		

Leviton Manufacturing Co., Inc.

201 North Service Road, Melville, NY 11747
Teléfono: +1-800-323-8920 · FAX: +1-800-832-9538 · Tech Line (8:30AM-7:30PM E.S.T. Monday-Friday): +1-800-824-3005

Leviton Manufacturing of Canada, Ltd.

165 Hymus Boulevard, Pointe Claire, Quebec H9R 1E9 · Telephone: +1-800-469-7890 · FAX: +1-800-824-3005 · www.leviton.com/canada

Leviton S. de R.L. de C.V.

Lago Tana 43, Mexico DF, Mexico CP 11290 · Tel.: (+52)55-5082-1040 · FAX: (+52)5386-1797 · www.leviton.com.mx

Visit our Website at: www.leviton.com

© 2018 Leviton Manufacturing Co., Inc. Todos los derechos reservados. Subject to change without notice.

Leviton has a global presence.

If you would like to know where your local Leviton office is located please go to: www.leviton.com/international/contacts/

