

Eaton HP404040SHL

Catalog Number: HP404040SHL

Eaton Cutler-Hammer series Housing panel, 400A, 120/240V, BRH/BWH Secondary Circuit, Aluminum Bus Material, Lever bypass, NEMA 3R Enclosure, Underground Feed Type, 22 kAIC Interrupt Rating, Surface mounting, Ringless Security, 1 Socket

General specifications

Product Name	Catalog Number
Eaton house panel	HP404040SHL
UPC	Product Length/Depth
782114105863	45.5 in
Product Height	Product Width
7.75 in	31.5 in
Product Weight	Warranty
110 lb	Eaton Selling Policy 25-000, one (1) year from the date of installation of the Product or eighteen (18) months from the date of shipment of the Product, whichever occurs first.
Certifications	
UL Listed	



Product specifications

Number of spaces

40

Interrupt rating

10 kAIC

Utility approvals

AR : Entergy

LA : Entergy

MS : Entergy

TX : Entergy

FL : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf Power, Oklahoma Gas and Electric)

IN : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf Power, Oklahoma Gas and Electric)

KY : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf Power, Oklahoma Gas and Electric)

NC : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf Power, Oklahoma Gas and Electric)

OH : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf Power, Oklahoma Gas and Electric)

SC : MEG (Duke Energy, Florida Power, Tampa Electric, Gulf Power, Oklahoma Gas and Electric)

FL : Tallahassee City Electric

HI : Hawaiian Electric

NC : Dominion

VA : Dominion

Bus material

Aluminum

Main circuit breaker

CSR2200

Enclosure

NEMA 3R

Security

Ringless

Amperage Rating

400 A

Line

Lug landings for compression, lugs not included

Mounting

Surface

Resources

Catalogs

[Eaton's Volume 1—Residential and Light Commercial](#)

Drawings

[Dimensional Drawing - METER BREAKER HP40SHL and HP404040SHL](#)

Specifications and datasheets

[Eaton Specification Sheet - HP404040SHL](#)

[Technical Data Residential Meter Breakers: Type CH and BR Residential](#)

Secondary circuit breaker

BRH/BWH

Type

House panel

Feed type

Bottom

Number of sockets

1

Used with

Type BR breakers

Bypass

Lever

Voltage rating

120/240 V

Number of circuits

40



Eaton Corporation plc
Eaton House
30 Pembroke Road
Dublin 4, Ireland
Eaton.com
© 2023 Eaton. All Rights Reserved.

Eaton is a registered trademark.

All other trademarks are
property of their respective
owners.



Eaton.com/socialmedia