



**Oh No!**  
IMAGE COMING SOON

## Formed Wire Top Tie, F-Neck Insulator

by FARGO  
Catalog ID: LDIF4502AS

F-Neck Insulator Top Tie for #4 ACSR, #3 AAC and #4 AAAC

- For securing bare or plastic jacketed conductor in the top groove of interchangeable headstyle insulators.
- F-Neck insulator: 2-7/8" neck diameter
- Recommended for use with ANSI Class 55-4 Pin, 55-5 Pin, 57-1 Pin, 57-2 Pin & 57-3 Pin Insulators.

### Product Details

#### General

Application	Top Tie
Color Code	Yellow / Orange
Insulator Throat Neck Type	F Neck
Material	Aluminum Clad Steel
Product Category	Ties
Type	Formed Wire
UPC	096359452768

#### Dimensions

Length	27.0 in
Weight	.190 lb

#### Conductor Related

Conductor Diameter - Maximum	0.277 in
Conductor Diameter - Minimum	0.245 in
Conductor Diameter Range	0.245 - 0.277
Conductor Type	ACSR, AAC, AAAC, Compacted ACSR, Compacted AAC and AWAC®

#### Logistics

Pallet Quantity	1600 EA
-----------------	---------

**For further technical assistance, please contact us**

#### Domestic Customer Service

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

#### International Customer Service

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)