



Oh No!
IMAGE COMING SOON

Formed Wire Top Tie, F-Neck Insulator

by FARGO
Catalog ID: LDIF4508AS

F-Neck Insulator Top Tie for 4/0 ACSR, 4/0 and 266.8 AAC, and 4/0 AAAC

- For securing bare or plastic jacketed conductor in the top groove of interchangeable headstyle insulators.
- F-Neck insulator: 2-7/8" neck diameter
- Recommended for use with ANSI Class 55-4 Pin, 55-5 Pin, 57-1 Pin, 57-2 Pin & 57-3 Pin Insulators.

Product Details

General

Application	Top Tie
Color Code	Yellow / Red
Insulator Throat Neck Type	F Neck
Material	Aluminum Clad Steel
Product Category	Ties
Type	Formed Wire
UPC	096359452799

Dimensions

Length	29.0 in
Weight	.380 lb

Conductor Related

Conductor Diameter - Maximum	0.588 in
Conductor Diameter - Minimum	0.521 in
Conductor Diameter Range	0.521 - 0.588
Conductor Type	ACSR, AAC, AAAC, Compacted ACSR, Compacted AAC and AWAC®

Logistics

Pallet Quantity	600 EA
-----------------	--------

For further technical assistance, please contact us

Domestic Customer Service

Hubbell Power Systems
210 N. Allen Centralia, MO 65240 USA
Phone: (573) 682-5521
Fax: (573) 682-8475
Email: hpscsc@hubbell.com

International Customer Service

Phone: +1-573-682-5521
Fax: +1-573-682-8516
Email: hpsintlcs@hubbell.com