



**Oh No!**  
IMAGE COMING SOON

# Formed Wire Top Tie, F-Neck Insulator

by FARGO  
Catalog ID: LDIF4513AS

F-Neck Insulator Top Tie for 636, 715.5, and 795 ACSR- 795 AAC

- For securing bare or plastic jacketed conductor in the top groove of interchangeable headstyle insulators.
- F-Neck insulator: 2-7/8" neck diameter
- Recommended for use with ANSI Class 55-4 Pin, 55-5 Pin, 57-1 Pin, 57-2 Pin & 57-3 Pin Insulators.

## Product Details

### General

|                            |                     |
|----------------------------|---------------------|
| Application                | Top Tie             |
| Color Code                 | Yellow / Green      |
| Insulator Throat Neck Type | F Neck              |
| Material                   | Aluminum Clad Steel |
| Product Category           | Ties                |
| Type                       | Formed Wire         |
| UPC                        | 096359452843        |

### Dimensions

|        |         |
|--------|---------|
| Length | 38.0 in |
| Weight | .440 lb |

### Conductor Related

|                              |  |
|------------------------------|--|
| Conductor Diameter - Maximum | 1.096 in   |
| Conductor Diameter - Minimum | 0.969 in   |
| Conductor Diameter Range     | 0.969 - 1.096  |
| Conductor Type               | ACSR, AAC, AAAC, Compacted ACSR, Compacted AAC and AWAC® |

### Logistics

|                 |        |
|-----------------|--------|
| Pallet Quantity | 600 EA |
|-----------------|--------|

**For further technical assistance, please contact us**

#### Domestic Customer Service

Hubbell Power Systems  
210 N. Allen Centralia, MO 65240 USA  
Phone: (573) 682-5521  
Fax: (573) 682-8475  
Email: [hpscsc@hubbell.com](mailto:hpscsc@hubbell.com)

#### International Customer Service

Phone: +1-573-682-5521  
Fax: +1-573-682-8516  
Email: [hpsintlcs@hubbell.com](mailto:hpsintlcs@hubbell.com)