

OLWX LED

Low Profile LED Wall Luminaires

Value and Versatility Defined

The OLWX LED wallpacks are energy-saving, long-life replacements for traditional metal halide wallpacks. The OLWX family is compact and powerful, delivering up to 18,200 lumens. The OLWX1 and OLWX2 offer several mounting options that provide versatility to meet your applications' needs.

Key Features:

- Energy savings up to 88% vs. comparable metal halide wallpacks; saves more than \$162 per luminaire, per year over 400W metal halide
- 20+ years expected service life (with lumen maintenance of L73/100,000 hours)
- Three wall mounting options and five flood mounting options provide exceptional versatility
- Easy to install with two set screws no need to open the luminaire

OLWX LED (5000K)							
Model	Input Watts	Lumens	Metal Halide Replacement				
OLWX1 13W	14W	1,289	70W				
OLWX1 20W	20W	2,663	175W				
OLWX1 40W	37W	4,079	250W				
OLWX2 90W	78W	10,000	400W <20' mounting height				
OLWX2 150W	147W	18,200	400W >20' mounting height				





OLWX1 replaces up to 250W MH

OLWX2 replaces up to 400W MH



Quick Facts:

- Replaces 70W 400W metal halide wallpacks
- Two product sizes
- Lumen packages ranging from 1,270 - 18,200 lumens
- 5000K CCT and 4000K CCT
- Can be inverted for uplight





OLWX LED Wall Luminaire

Ordering Information

EXAMPLE: OLWX2 LED 150W 50K DDB

OLWX1 LED & OLWX2 LED						
Series	Performance Package	Color temperature	Voltage	Control Options	Finish	
OLWX1 LED	13W 20W 40W	40K 4000K ¹ 50K 5000K	(blank) MVOLT ² 120 120V ³ 347 347V	(blank) none PE 120V Button Photocell ^{1,3}	DDB Dark bronze	
OLWX2 LED	90W 150W					

Flood Light Accessories					
OLWX1TS	Slipfitter – size 1				
OLWX1YK	Yoke – size 1				
OLWX1THK	Knuckle – size 1				
OLWX2TS	Slipfitter – size 2				
OLWX2YK	Yoke – size 2				

Ν	otes	

- 1 Not available with 347V option
- 2 MVOLT driver operates on any line voltage from 120-277V (50/60Hz)
- 3 Specify 120V when ordering with photocell (PE option)

Wall Mounting Options





Wiring Box for Conduit

Mounting Plate Inverted



Flood Mounting Options



Slipfitter**





Knuckle (OLWX1 only)**


** Top Visor & Vandal Guard**

** Flood mounting accessories sold separately. Top Visor and Vandal Guard included with purchase of any flood mount accessory.

Product Dimensions

OLWX1









OLWX2









Learn more about our LED floodlighting solutions at www.lithonia.com

