SC816F150PS

Homeline All In One combination service entrance device, ringed socket, no bypass, OH, UG, 150 A, 8 spaces, solar ready





Main	
Product or component type	Meter Mains
Range of product	Homeline
Includes	Circuit breaker 1) 2P 150 A 120/240 V AC main supply ready assembled

Complementary

Line Rated Current	150 A
Short-circuit current	22 kA
Network number of phases	1
Meter socket type	Ringed
Mounting	Surface
Number of spaces	8
Number of circuits	16
Number of Tandem Breakers	8
Hub type	A-L
Electrical connection	Lugs line side Lugs service ground Feed-thru lugs load side
Wire Size	AWG 4250 kcmil aluminium/copper)line side AWG 6250 kcmil aluminium/copper)load side AWG 14AWG 2/0 aluminium/copper)service ground
Tightening torque	Main lugs 250 lb.in, AWG 4250 kcmil, aluminium/copper Service ground 50 lb.in, AWG 14AWG 2/0, copper Service ground 50 lb.in, AWG 12AWG 2/0, aluminium Lugs 250 lb.in, AWG 6250 kcmil, aluminium/copper Branch lugs 50 lb.in, AWG 14AWG 2/0, copper Branch lugs 50 lb.in, AWG 12AWG 2/0, aluminium Cover 10 lb.in
Disconnect	Service disconnect (factory installed)
Main Breaker Rating	200 A
Branch Breaker Rating	110 A
Service feed location	OH UG
Bypass type	No bypass
Maximum Depth	6.30 in (160.02 mm)
Maximum Width	21.50 in (546.10 mm)
Maximum Height	30.26 in (768.60 mm)

Environment

NEMA degree of protection	NEMA 3R
Product certifications	UL E-6294

Ordering and shipping details

Category	00148 - HOMELINE CSED DEVICES
Discount Schedule	DE3A
GTIN	00785901278399
Package weight(Lbs)	53 lb(US) (24.04 kg)
Returnability	Yes

Offer Sustainability

Green Premium product	
☑ REACh Declaration	
Yes	
Compliant EPEU RoHS Declaration	
Yes	
₽¥Yes	
China RoHS Declaration	
Product Environmental Profile	
	REACh Declaration Yes Compliant E EU RoHS Declaration Yes Yes China RoHS Declaration