



PC2440W



Product Description

4" dia. round fixture support box for use with nonmetallic sheathed cable

Brand: flexBOX®
Catalog #: PC2440W

Carton Quantity: 24
Carton Weight: 7 lb.

Width: 4 in.
Depth: 3 in.
Volume: 24.5 cu. in.
Type of Installation: Old Work
Round Ceiling Box

UPC: 085339983118
UNSPSC: 39121316
Patents:
U.S. Patent No. 6,365,831 B1
Country of Origin: United States of America

FEATURES

Machine tapped fixture holes, round exterior for easy cut-in

APPLICATION

Old work residential construction 2 HR fire resistive walls

STANDARDS

ANSI / UL 514C: File No. E30594



FIRE CLASSIFICATION

Fire Test of Building Construction Materials

ANSI / UL 263: File No. CEYY.R9379 (Category / File No.)

Note: Products must also be certified to: ANSI / UL 514C

Fire Resistance Classification in Floor-Ceiling Assemblies 2-Hours or Less

Distance between boxes in adjacent cavities may be reduced to 5 ½ inches

Note: For more details please refer to the UL fire resistive directory and Allied Moulded's CEYY.9379 (Outlet boxes and fittings classified for fire resistance)

COLOR

Black

ADDITIONAL MATERIALS

Galvanized steel brackets and plated carbon steel fasteners

MATERIAL

Polycarbonate

SUPPORT RATING

Meets NEC for wall applications

MOUNTING

Metal wing brackets/nonmetal ears wall compression