

Product availability : Stock - Normally stocked in distribution facility



Price* : 1682.00 USD



Main

| | |
|--------------------------------|-------------------------|
| Product or component type | Motor Circuit Protector |
| Range of product | PowerPact H |
| Trip unit technology | Magnetic |
| Breaking capacity code | J |
| Accessory / separate part type | Alarm switch |

Complementary

| | |
|-----------------------------------------------------|--------------------------------------------------------------|
| Line Rated Current | 50 A |
| Poles description | 3P |
| Breaking capacity | 65 kA at 480 V AC 25 kA at 600 V AC 100 kA at 240 V AC |
| System Voltage | 600 V AC |
| [Ics] rated service short-circuit breaking capacity | 80 % |
| Mounting mode | Unit mount |
| Electrical connection | Lugs load Lugs line |
| AWG gauge | AWG 14...AWG 3/0 (aluminium/copper) |
| Magnetic hold current | 14...42 A |
| Magnetic tripping current | 84...546 A |

Environment

| | |
|---------------------------------------|-----------------|
| Product certifications | CE IEC UR |
| Ambient air temperature for operation | 104 °F (40 °C) |

Disclaimer: This documentation is not intended as a substitute for and is not to be used for determining suitability or reliability of these products for specific user applications

Ordering and shipping details

| | |
|-----------------------|---------------------------------------------|
| Category | 01125 - HJ, JJ UNT MNT MTR CIRCUIT PROTECTR |
| Discount Schedule | DE2 |
| GTIN | 00785901437543 |
| Nbr. of units in pkg. | 1 |
| Package weight(Lbs) | 5 |
| Returnability | N |
| Country of origin | US |

Offer Sustainability

| | |
|----------------------------------|---------------------------------------------------------------------------------------------------------------------------------------|
| Sustainable offer status | Green Premium product |
| RoHS (date code: YYWW) | Compliant - since 0832 - Schneider Electric declaration of conformity Schneider Electric declaration of conformity |
| REACH | Reference not containing SVHC above the threshold Reference not containing SVHC above the threshold |
| Product environmental profile | Available |
| Product end of life instructions | Need no specific recycling operations |

Contractual warranty

| | |
|-----------------|-----------|
| Warranty period | 18 months |
|-----------------|-----------|