

YTS39RT43RSHT

by Burndy
Catalog ID: YTS39RT43RSHT

Prop 65 Notice

Full Tension ACSS EHV Splice Kits, YTS39RTH Aluminium Sleeve (Qty. 1), YTS43RS Steel Sleeve (Qty. 1), PARAKEET 556.5 (24/7) kcmil; DOVE 556.5 (26/7) kcmil



Product Details

General

Application	For ACSS Conductor, Corona free operation up to 550 KV
Connector Type	Splice
Die Index	722;723
Die Type	L722 for Aluminium Sleeve, L723 Steel Sleeve
Material	Aluminum
Trade Name	HYSPLICE™
UPC	621945461611
UPC 12 Digit	781810515549

Dimensions

Dimension - B Length inch	2.47 in
Dimension - Length Overall inch	28.74 in
Dimension - Outside Diameter inch	1.50 in

Electrical Ratings

Voltage - Maximum	550 kV
-------------------	--------

Conductor Related

Conductor - ACSS Str Size	PARAKEET 556.5 (24/7) kcmil; DOVE 556.5 (26/7) kcmil
Conductor - ACSS Str Size Range	556.5 (24/7) kcmil-556.5 (26/7) kcmil
Conductor - Material	Aluminum

Certifications and Compliance

Certification - CSA Approved	No
------------------------------	----

Logistics

Minimum Pack Quantity	1
-----------------------	---

For further technical assistance, please contact us

BURNDY Headquarters

47 East Industrial Park Drive
Manchester, New Hampshire 03109

Customer Service Hours:

8 AM - 8 PM Eastern Monday-Friday
Emergency Service 24-hours/365 Days
Phone: 1-800-346-4175
1-603-647-5299 (International)