



NUVO SERIES FOUR 6.5" DVC IN-CEILING SPEAKERS

NV-4IC6-DVC |

FEATURES & BENEFITS

The NV-4IC6-DVC utilizes two Aluminum tweeters and a 6.5" dual voice coil Glass Fiber Woofer. This speaker offers a super clean look, and is finished beautifully with their completely rimless, magnetic grills. They also offer quick and secure installation by utilizing three dog legs, instead of the usual four, and includes a unique tweeter bridge that maximizes sound quality, looks great, and serves as a handle to hold the speaker by during installation.



- 8 ohm rated
- Single stereo speaker
- Three dog leg design for easy installation
- Magnetic rimless and paintable grill
- Unique tweeter bridge that also doubles as an installation handle
- Lifetime Warranty

SPECIFICATIONS

Wattage: 75W rms
Maximum Wattage: 150W Peak
Woofer Diameter: 6.5" (165mm)
Woofer Composition: Kevlar/Glass Fiber
Surround Material: Rubber
Number of Woofers: 2
Tweeter Size: 0.75" (19mm)
Tweeter Composition: Aluminum Dome
Number of Tweeters: 1
Decibels: 88 dB
Sensitivity: 88 dB (1 watt/meter)
Impedance: 8Ω
Frequency Response: 55 Hz - 20 KHz (+/- 3dB)

Cutoff Frequency: 2.7 KHz

GENERAL INFO

Color: White

Type: Indoor, In-Ceiling, Round

Special Features: Magnetic thin bezel, Kevlar/Glass woofer, Aluminum dome tweeter, steel powder coat grill, pivoting tweeter, adjustment switches

LISTING AGENCIES/THIRD PARTY CERTIFICATIONS

RoHS: Yes

DIMENSIONS

Depth (Metric): 100mm

Depth (US): 3.94"

Height (Metric): 230mm

Height (US): 9.06"

Length (Metric): 99mm

Length (US): 3.90"

Width (Metric): 230mm

Width (US): 9.06"

TECHNICAL INFORMATION

Frequency Response: 55 Hz - 20 KHz (+/- 3 dB)

Material: ABS frames and stamped metal baskets

Mounting: Cutout Round: 8.07" (205mm)

NEMA Rating: 5WD Wiring Devices, Building Systems

Speaker Impedance Load: 8Ω

Tweeter Type: Aluminum Dome

Watts: 75W RMS

Woofer Type: Glass Fiber